

LEGENDARY PERFORMANCE™

PS Audio Scandinavia

0045 21750252 ps@psaudio.dk www.psaudio.dk

POWER AMPS

	I OWER AND O	MODE	
Unit	Description	MSRP	DKK
MC2KW	•1 x 2000 Watts • Reference Series	kr.	396.000,00
	• Quad-Balanced Design		
	Separate Positive & Negative Amplifiers		
0.00	• 3 Full Sets of Terminals for Tri-Wiring @ 8, 4 & 2 Ohms		
-	• Silent Convection Cooling • Safe Operation to Below 2 Ohms		
MC1.25KW		kr.	123.750,00
	NEW • 1 x 1200 Watts • Redesigned from top to bottom • Autoformer for 2, 4 & 8 Ohms • Exclusive McIntosh Power Assura		
	System • Direct LED Backlighting • 50% increase in filter capacity from previous model • McIntosh Monogrammed		
	Heatsinks™ • Updated power transformer, internal wiring, circuit components and industrial design • Power management		
and the same	system • Power Guard®		
o o	• Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts		
MC611		kr.	74.250,00
	NEW • 1 x 600 Watts • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Direct LED Backlighting • 2x f		
	capacity from previous model results in 55% increase in dynamic headroom from 1.8dB to 2.8dB • McIntosh Monogramm		
	Heatsinks™ • ThermalTrak™ Output Transistors • Updated internal wiring, circuit components and industrial design •		
0 0	Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts		
MC601		kr.	69.300,00
	Output Autoformers for 2, 4 & 8 Ohms		
	Peak-Responding Wattmeter		
	ThermalTrak™ Output Transistors		
A CONTRACTOR OF THE PARTY OF TH	• 90 amps Output Current Capability		
ō = ō	Over 140 Joules of Energy Storage		
	Patented McIntosh Speaker Binding Posts		
MC301		kr.	49.500,00
	• 1 x 300 Watts • Quad-Balanced Design • Slim Chassis Design		
	Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter		
	 Power Guard to Prevent Clipping • ThermalTrak™ Output Transistors 		
2000	Patented McIntosh Speaker Binding Posts		
	, · · ·		
MC2301	•1 x 300 Watts •Balanced Unity-Coupled Vacuum Tube Design	kr.	118.800,00
	•Peak Responding Wattmeter		
100	•Two Balanced Inputs/Outputs		
(Care	Remote Power Control with Meter Light Control		
CO Tron C	Large Gold Plated Five-Way Binding Posts		
	•½" Thick Glass Front Panel with Tube View		
MC75		kr.	37.125,00
- F			
199	DISCONTINUED Availability subject to stock on hand		

POWER AMPS

Unit	Description	MSRP	
MC452	•2 x 450 Watts • Quad-Balanced Design	kr.	84.150,00
	Output Autoformers for 2, 4 & 8 Ohms		
27 1111 242	Peak-Responding Wattmeters		
	 ThermalTrak™ Output Transistors 		
ō = ō	• 75 amps Output Current Capability		
	Over 200 Joules of Energy Storage		
	Patented McIntosh Speaker Binding Posts	1.	04.050.00
MC302	Output Autoformers for 2, 4 & 8 Ohms	kr.	64.350,00
	 ThermalTrak™ Output Transistors 		
	60 amps Output Current Capability		
ō — ō	Over 140 Joules of Energy Storage		
	Patented McIntosh Speaker Binding Posts		
MC152		kr.	44.550,00
	•2 x 150 Watts • Slim Chassis Design	1	
	 Output Autoformer for 2, 4 & 8 Ohms Peak-Responding Wattmeter 		
	 Power Guard to Prevent Clipping • ThermalTrak™ Output Transistors 		
o	Patented McIntosh Speaker Binding Posts		
MC275		kr.	54.450,00
WIC275	•Version VI Model• Same feature set as MC275LE but with polished stainless chassis	NI.	34.430,00
	•2 X 75 Watts •Outputs for 4, 8, 16 Ohms •Sentry Monitor Protection		
20.	 Unique Tube Illumination to Indicate Operational Status 		
Onto	•Front Apron Power Switch •Stereo/Mono Switch		
The state of the s	•Patented McIntosh Speaker Binding Posts		
	 Power Control to Enable Remote On/Off with McIntosh Preamplifiers 		
MC303	•3 x 300 Watts •Output Autoformers	kr.	108.900,00
100000000000000000000000000000000000000	Peak Responding Wattmeters • LED Fiber-Optic Illumination		,
COMPANIES COMPANIES	*Exclusive McIntosh Power Assurance System		
	•60 Amps Output Current		
0 0	 Large Gold Plated Five-Way Binding Posts 		
MC205	3 x 200 Watts *Two-Zone Operation	kr.	69.300,00
	•DPM Circuit Design Ensures Full Power at 4 or 8 Ohms		,
	•Peak Responding Wattmeters •LED Fiber-Optic Illumination		
Reaction Comment	•Exclusive McIntosh Power Assurance System		
T w Didea T	•Remote Power Control Trigger		
	•Multi-Way Speaker Binding Posts		
MC207	•7 x 200 Watts •Two-Zone Operation •DPM Circuit Design Ensures Full Power at 4 or 8 Ohms	kr.	89.100,00
	Peak Responding Wattmeters •LED Fiber-Optic Illumination		
	•Exclusive McIntosh Power Assurance System		
Some Some	•Remote Power Control Trigger		
, O O	•Multi-Way Speaker Binding Posts		
1100007	i i i	1	FO 400 00
MC8207	•7 x 200 Watts •Two-Zone Operation	kr.	59.400,00
AVE 314 315	•DPM Circuit Design Ensures Full Power at 4 or 8 Ohms		
	•Theater-Friendly LED Meters •LED Fiber-Optic Panel Illumination	1	
THE PERSON NAMED IN	•Exclusive McIntosh Power Assurance System		
	•Remote Power Control Trigger •Multi-Way Speaker Binding Posts		
	IVIUII-VVAV SDEAKEI BINGING POSIS		

INTEGRATED AMPLIFIERS

Unit	Description	MSRP	
MA9000	•2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 2 High-Level Balanced Inputs • MC & Phono Inputs (both adjustable loading) • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 8-Band Equalizer • Premium gold-plated solid brass analog connectors • ¼" High Drive Headphone Jack with Headphone Crossf Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Solid Cinch™ speaker binding posts • Upgraded audio components	kr.	103.950,00
MA8900	•2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & Phono Inputs • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192k DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 5-Band Equalizer • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components	kr.	74.250,00
MA7900	DISCONTINUED Availability subject to stock on hand	kr.	69.300,00
MA5300	NEW • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • 4 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • D Digital Audio Module w/ 6 inputs • DSD256 & DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balan mode • McIntosh Monogrammed Heatsinks™ • ½" High Drive Headphone Jack w/ Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Bass & Treble tone controls	kr.	49.500,00
MA252	NEW • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • Hybrid: Vacuum Tube preamp + solid state power amp • (2) 12AX7a & (2) 12AT7 vacuum tubes in preamp • Direct couple amp • 2 Unbalanced & 1 Balanced Inputs • Moving Magnet I • Bass & Treble tone controls • McIntosh Monogrammed Heatsinks™ • ½" High Drive Headphone Jack • Power Guard® • Sentry Monitor™ • Power Control • Retro styling • Die cast aluminum name badge on each side • Remote control	kr.	34.650,00
MA7200	NEW • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Baland mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • ½" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components	Not ava or Cana	ilable in US da

RECEIVERS

Unit	Description	MSRP	
MAC7200		kr.	69.300,00
Parket Company	NEW • 2 x 200 Watts • Built in AM/FM Tuner • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • '¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components		

HEADPHONE AMPLIFIERS

Unit	Description	MSRP	
MHA150	Headphone Amplifier • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms Headphone Crossfeed Director (HXD®) images quality recordings like conventional speakers • Power Guard • 50 Watt stereo speaker terminals • Compact size for placement flexibility • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport	kr.	44.550,00
MHA100	DISCONTINUED Availability subject to stock on hand	kr.	44.550,00
MHA50	NEW • Portable Decoding Amplifier • Comparably sized to smartphones • Inputs: wired inputs for iOS devices & Andro devices with USB On-The-Go technology; Mac® & Windows® PCs; Bluetooth® 4.1 with aptX™ • 3.5mm gold plated headphone jack • High-performance DAC supports 32-bit/192kHz hi-res audio, up to DSD128 & DXD384 files & asynchror USB audio • Up to 6 hours of playback on a single battery charge • 2 gain settings drive 8-600 Ohms • Headphone Crossf Director (HXD®) • Includes: leather case; 4 USB adapter cables; wall mount charger	kr.	6.930,00

HEADPHONES

Unit	Description	MSRP	
MHP1000		kr.	19.800,00
	 Same superior sound characteristics as McIntosh speakers 		
	 Closed headphone design isolates outside noise and distractions 		
	 Lightweight design and minimal clamping pressure permit long, relaxing listening sessions 		
	 Headband and ear pads are a premium, natural, soft leather for luxurious comfort 		
	 Engineered to work with any current or legacy McIntosh headphone amplifier 		
	Cables included: one 1 meter w/ 3.5mm stereo connector; one 3 meter w/ 6.3mm stereo connector		

AUDIO PREAMP CONTROL CENTERS

Unit	Description	MSRP	
C1100C	Controller for Reference series multi-chassis C1100T Vacuum Tube Preamp Keeps control & power sections separate from the audio section • Left & right channels are electrically & mechanica isolated from each other to allow true dual mono operation Connected to C1100T by specially designed, shielded & high performance umbilical cables Requires use of C1100T	kr.	64.350,00
C1100T	• Vacuum Tube Preamp to be used with C1100C Controller • High level inputs have the lowest noise of any McIntosh preamplifier ever produced • 6 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 12 vacuum tubes • 2 Balanced (XLR) Outputs • 2 Unbalanced Outputs • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • Requires use of C1100C	kr.	64.350,00
D1100	• Reference Level Digital Preamplifier with our most advanced DAC • 8-channel, 32-bit DAC is used in Quad Balanced mc Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • 9 Inputs: 3 coax, 3 optical, 1 each MCT (for SACI playback from MCT450 Transport), AES/EBU & USB • 3 sets of Balanced and Unbalanced stereo outputs (1 set fixed volu 2 sets variable) • 1 Headphone Jack (½") with Headphone Crossfeed Director (HXD®) • Audio channels & power supplies electrically isolated from each other for dual mono operation • Can be used by itself or in tandem with analog C1100 Vaca Tube Preamp • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis • RS232	kr.	69.300,00
C2600	Vacuum Tube Preamplifier • 3 Balanced (XLR) Inputs • 3 Balanced (XLR) Outputs • 3 Optical & 2 Coax Inputs at 24-bit/192kHz • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT Transport • Supports DSD64, DSD128, DSD256, DX 352.8kHz & DXD 384kHz • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • Output Meters	kr.	69.300,00
C47	• 2 Balanced (XLR) Inputs • 2 Unbalanced Inputs • MC & MM Phono Inputs • 2 Balanced (XLR) Outputs • 2 Unbalanced Outputs • 2 Optical & 1 Coax Inputs at 24-bit/192kHz • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD)	kr.	39.600,00
C52	• 3 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced (XLR) Outputs • 3 Unbalanced Outputs • 3 Optical & 2 Coax Inputs at 24-bit/192kHz • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • 8 Band Equalizer • Output Meters	kr.	69.300,00
C22	Vacuum Tube Stereo Preamplifier • 6 Unbalanced Inputs • 2 Balanced (XLR) Inputs Moving Magnet and Moving Coil Phono Inputs • 1 Pair Balanced (XLR) Outputs 3 Pairs of Unbalanced Outputs: 2 Pairs Switched + 1 Pair Fixed Front Panel Headphone Jack • Retro Design	kr.	59.400,00

AUDIO PREAMP CONTROL CENTERS

Unit	Description	MSRP	
D150		kr.	29.700,00
	Digital Stereo Preamplifier • Supports DSD64, DSD128, DXD 352.8kHz and DXD 384kHz		
	 6 Digital Inputs: 2 Coaxial, 2 Optical, 1 USB and 1 DIN 		
A PART OF THE PART	• 1 Set Each: Balanced & Unbalanced Fixed and Balanced & Unbalanced Variable Audio Outputs		
EQ ui min i Q	 Power and Data Control Ports • Compact Form Factor of just under 4" in Height 		
	• 8 Channel, 32-bit, 500kHz D/A Converter with Wide Dynamic Range and Extremely Low Distortion		

PHONO PREAMPLIFIERS

Unit	Description	MSRP	
MP1100	Dedicated Vacuum Tube Phono Preamplifier • Fully Balanced Vacuum Tube Phono Stage • Four 12AX7A Vacuum Tube tubes per channel) • 3 sets of RCA Phono Inputs (XLR connectors available on 1 of the inputs) • 4 Pre-Programmed & 5	kr.	79.200,00
	Programmable Profiles • 8 Capacitance & 7 Resistance Settings • 5 Analog Equalization Curves • 2 Analog Noise Filte Adjustable Gain • 1 pair of Balanced & Unbalanced Line Inputs & Fixed Outputs • Coax, Optical & USB Digital Outputs • R computer via USB • Digital Output Clipping Indicator • Mono setting • Dual Mono design • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis		
MP100	Dedicated Phono Preamplifier • Adjustable Moving Coil & Moving Magnet inputs (6 settings each) • Balanced & Unbala Analog Ouputs • Coax, Optical and USB Digital Outputs Rip to computer via USB • Digital or clipping indicator • Mono switch • Narrow chassis	kr.	19.800,00

AUDIO VIDEO CONTROL CENTER/ROOM CORRECTION SYSTEM

Unit	Description	MSRP	
MX160		kr.	138.600,00
	• 16 Channel A/V Processor used in 11.1 (aka 7.1.4) w/ 4 AUX channels (all 16 are balanced) • Supports Dolby Atmos, Auro-3D & DTS-HD Master Audio with planned upgrade for DTS:X • Supports 4K Ultra HD native sources plus upscaling of lower resolutions • 3D video supported • Built in RoomPerfect room correction • 8 HDMI inputs & 4 HMDI outputs (all HDCP 2.2) • HDBaseT output • 2 sets of stereo balanced, 4 sets of stereo unbalanced, dedicated phono & 7.1 multi-channel unbalar inputs • 4 optical, 3 coax & 1 XLR digital audio inputs • Supports DSD64, DSD128, DXD 352.8kHz and DXD 384kHz via USB • Supports 5 zones with independent audio & vic plus additonal audio only zone		

AUDIO VIDEO CONTROL CENTER/ROOM CORRECTION SYSTEM

Unit	Description	MSRP	
MX122		kr.	69.300,00
O dra O	•13 Channel A/V Processor used in 11.2 (aka 7.2.4) • Dolby Atmos with planned upgrades for DTS:X & Auro-3D • Supports Ultra HD native sources plus upscaling • 3D video supported • HDMI: 7 inputs & 3 outputs (all HDCP 2.2, HDR, 4K Ultra HD at 50/60Hz, 4:4:4 color, Rec. 2020) • Inputs: 1 stereo balanced • 7 stereo unbalanced + 1 dedicated phono • 7.1 multi-channel unbalanced • 3 component • composite • 2 optical & 2 coax digital audio inputs • DSD64 via USB • Audyssey MultEQ XT32 room correction • Bluetoc Airplay • Interfaces to Pandora, SiriusXM & Spotify + vTuner • Stereo audio & video for Zone 2 + stereo audio for Zone 3 band equalizer		
MEN220	RoomPerfect Room Correction Custom EQ Application (that runs on any Windows PC) 2-Way Crossover for true bi-amping of any loudspeaker Audio Inputs: 2 Single-Ended & 2 Balanced Audio Outputs: High-Pass: 2 Single-Ended & 2 Balanced	kr.	49.500,00

SOURCE COMPONENTS

Unit	Description	MSRP	
MCD550	-2-Channel CD / SACD Player -8 Channel, 32 Bit/192kHz, PCM/ DSD Digital Audio Converter (decodes PCM signals from CDs and digital inputs; DS signals from SACDs) - USB Audio Digital Input Accepts Data Rates Up to 24-Bit/192kHz - Both Stereo Balanced and Unbalanced Analog Outputs - Built-In Headphone Amplifier	kr.	64.350,00
MCD350	2-Channel SACD/CD Player 2-Channel, 32-bit/192kHz balanced PCM/DSD DAC (decodes PCM signals from CDs; DSD signals from SACDs) • Fixe analog stereo balanced and unbalanced outputs • Digital coax and optical outputs • 2x read speed for better reading of damaged CDs and CD-R/RWs	kr.	49.500,00
MCT500	NEW • 2-Channel SACD/CD Transport • Digital balanced, coax, optical & MCT outputs • Unique MCT output connects to select McIntosh models with a MCT input for playback of SACD high definition audio • Plays SACD, CD, CD-R/RW & DVI Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • 2x read speed	kr.	44.550,00
MCT450	• 2-Channel CD / SACD Transport • Digital balanced, coaxial, optical and DIN outputs • Unique DIN output connects to select McIntosh models with a DIN for the purist possible sound quality • Plays SACD, CD, CD-R & CD-RW • Premium aluminum die cast CD tray provides the best handling of music discs • 2x read speed for better reading of damaged CDs and CD-R/RWs	kr.	39.600,00
MCT80	NEW • 2-Channel SACD/CD Transport sized to match MXA80 Integrated Audio System • Digital coaxial, optical and MC (DIN) outputs • Unique MCT output connects to select McIntosh models with a MCT input for the purist possible sound quate Plays SACD, CD, CD-R/RW & user generated DVD or CD Data Discs • Die-cast aluminum tray • Advanced digital servo faster, quieter & accurate operation • 2x read speed for better reading of damaged CDs & CD-R/RWs	kr.	34.650,00

SOURCE COMPONENTS

Unit	Description	MSRP	
MVP901	Universal Blu-ray DVD/CD Player • Upsamples to 4K Ultra HD • 3D Video • Built in decoding of Dolby True HD & DTS-H Master Audio + legacy formats • Passes object-based 3D audio formats Dolby Atmos, DTS:X & Auro-3D to compatible processor • Fast Disc Loading • Quad Balanced 32-bit/192kHz DAC for stereo playback of CD/SACD/DVD-Audio disc: • BD-Live & File Sharing Over Home Network	kr.	54.450,00
MR87	AM/FM/HD Radio Tuner with Multi-Casting • XM-ready Illuminated Analog Dial and 2-Line Multi-Function Fluorescent Display • Smooth-Acting, Weighted Tuning Mechanism Animated Dial Pointer • Dual-Differential Remote AM Antenna • External AM and FM Antenna Inputs • 60 Station Presets (20 per band) • Balanced and Single-ended Analog Output • Coaxial and Optical Digital Audio Output	kr.	44.550,00
MT10	Belt-Drive Tumtable Dural Aluminum Tone Arm Weight-Matched Moving Coil Cartridge Included Precision AC Motor Magnetic Spindle Bearing Strobe Speed Control Illuminated Speed Meter Multi-Layered Damped Chassis	kr.	103.950,00
MT5	Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Magnetic Spindle Bearing • Multi-Layered Damped Chassis • Inclu Plexi Dustcover	kr.	64.350,00
MT2	Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • Plays 33-1/3 and 45 rpm records • High-Output Moving Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Resonance optimized and highly compressed wood base with black lacquer finish • Includes Plexi Dustcover	kr.	39.600,00

INTEGRATED AUDIO SYSTEMS

Unit	Description	MSRP	
McAire	Built in AirPlay® allows wireless streaming of music via Wi-Fi network from Mac or PC based iTunes® library, iPad© iPhone® or iPod touch® USB docking is available for all day playback and charging Computers and TVs may be quickly connected for full range, high fidelity sound Two 4" woofers, two 2" midranges, two 3/4" tweeters Delivers the legendary McIntosh look and sound quality in a compact size	kr.	29.700,00
MXA70	DISCONTINUED Availability subject to stock on hand	kr.	59.400,00
MXA80	• Compact System • 2 x 50 Watts • Pair of specially designed 8 Ohm 2-way speakers • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD) images high quality recordings like conventional speakers • Power Guard to Prevent Clipping and Speaker Damage • 5 Step Bass Boost Control • Polished Stainless Steel Chassis	kr.	59.400,00

MEDIA STREAMERS

Unit	Description	MSRP	
MB50		kr.	19.800,00
	*NOT AVAILABLE IN ALL TERRITORIES • Streaming audio player featuring DTS Play-Fi technology • Connects to existi Wi-Fi to turn traditional audio system into a wireless audio system • Free Apple & Android app to stream music library st on mobile device • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QCMus Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Analog & digital inputs for mini-preamp functional Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • Narrow chassis		
MB100	Enjoy favorite web based & hard drive stored music in McIntosh sound at up to 24 bit/192kHz On-board embedded streaming services: Pandora®, SiriusXM®, Spotify®, Rhapsody & TuneIn Synchronizes content stored on networked computers so it is readily playable Guest provided music can be streamed via AirPlay Amazon Cloud Drive or Apple iCloud for secure content backup Connect external hard drives or flash drives via 4 USB and 1 eSata ports	kr.	59.400,00

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	MSRP	
XRT2.1KL	NEW • Reference Series Dual-Column 4-Way Ported Line-Source • 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3/4" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Left speaker only (see XRT2.1KR for matching right speaker)	kr.	643.500,00
XRT2.1KR	NEW • Reference Series Dual-Column 4-Way Ported Line-Source • 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3/4" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Right speaker only (see XRT2.1KL for matching left speaker)	kr.	643.500,00
XRT2K Refunished	DISCONTINUED Availability subject to stock on hand	kr.	544.500,00
XCS2K	DISCONTINUED Availability subject to stock on hand_	kr.	396.000,00

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	MSRP	
XCS1K Refurbished	DISCONTINUED Availability subject to stock on hand	kr.	222.750,00
XCS200 Refurbished	DISCONTINUED Availability subject to stock on hand_	kr.	69.300,00
CK200	In Wall Mounting Kit forXCS200	kr.	6.930,00

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	MSRP	
RS100	*NOT AVAILABLE IN ALL TERRITORIES* Wireless speaker featuring DTS Play-Fi technology * Start with 1 then add more build system * Up to 16 can be added to a Wi-Fi network * Connect to existing Wi-Fi & then stream music library from mo device via free Apple & Android app * App has built-in support for leading streaming services including Deezer, KKBo Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) * Lossless playback of up to 1 bit/48kHz * Playback support for high-resolution music up to 24-bit/192kHz * AUX input for non-streaming use * Subwoo output	kr.	9.900,00
XR50	True 3-Way Compact Bookshelf Speaker • 40 Hz - 45 kHz Frequency Response 1 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters 1 x 3/4" Titanium Super Tweeter• 300-Watt Music Power-Handling Patented McIntosh Binding Posts Front-Panel McIntosh Logo Illumination using Power Control Premium cabinet finishes include Red Walnut, Gloss Black	kr.	19.800,00
XR100	True 4-way Floor-Standing Tower Speaker • 30 Hz - 45 kHz Frequency Response 4 x 6"LDHP Woofers • 8 x 2" Titanium Midrange Super Tweeter Dual Sets of Patented McIntosh Binding Posts Enable Bi-Wire or Bi-Amplification 600-Watt Music Power Handling • Front-Panel McIntosh Logo Illumination Using Power Control • Premium Cabinet Finishes Include Red Walnut, Gloss Black	kr.	49.500,00
LCR80	True 3-Way Center-Channel Speaker • 80Hz to 45 kHz Frequency Response • 2 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 300-Watt Music Power-Handling • Voiced to Match XR50 & XR100 • Patented McIntosh Binding Posts • Premium Cabinet Finishes include Red Walnut, Gloss Black (Pear Maple Discontinued)	kr.	24.750,00

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	MSRP	
HT30-IW	IN-Wall THX Licensed Dipole Surround Speaker 200 Watts Max Continuous Power 2 x 5" Polypropylene Woofers Paintable Frame & Metal Grill SOLD IN PAIRS	kr.	27.720,00
HT30-OW	ON-Wall THX Licensed Dipole Surround Speaker 200 Watts Max Continuous Power 2 x 5" Polypropylene Woofers 2 x 1" Aluminum Dome Tweeters Paintable Frame & Metal Grill SOLD IN PAIRS	kr.	27.720,00
RK100	New Construction Rough-In Kit for CS100	kr.	445,50
WS350	IN-Wall 3-Way Speaker 200 Watts Max Continuous Power Handling 5-Tweeter Bessel Array One 8" Woofer • One 4" Midrange • Five 1" Dome Tweeters Deep-Drawn Sealed Aluminum Enclosure Paintable Frame & Metal Gille	kr.	21.780,00
RK320	RETURNED TO ACTIVE PRODUCTION	kr.	445,50

ACCESSORIES

Unit	Description	MSRP	
MPC1500	 AC Isolation Transformer & AC Switching Hub 12 Rear Panel AC Outlets with Programmable Power Control Options Front and Rear Panel LED Status Indicators Front Panel Back-Lit Meters Display Line Voltage & Amperage 	kr.	49.500,00
MC CLOCK	The Mcintosh Clock boast our trademak glass front pannel and two of our blue meters , One to show the hour and the other to show minutes.	kr.	17.820,00
LB100	Unmistakably McIntosh. The LB100 Light Box proudly displays the "Handcrafted In The USA Since 1949" statement as badge of honor. A must for every McIntosh owner. Approximately the size of a McIntosh CD player. Includes Power Control for seamless on/off with other McIntosh components.	kr.	14.850,00
BLI-23 (pair)	Balanced Line Integrator, 2 XLR Inputs & 3 XLR Outputs	kr.	2.970,00
MCBOOK IlkIntosh	"For the Love of Music" The History of McIntosh	kr.	1.485,00
TM3 Tuner Module	AM/FM/HD Radio Tuner Module for use with MA6600 Integrated Amplifier Includes Dual-Differential Remote AM Antenna External AM and FM antenna inputs	kr.	7.920,00

AUDIO CABLES

Unit	Description	MSRP	
CBA1M	BALANCED AUDIO SINGLE 1-METER	kr.	3.960,00
CBA2M	BALANCED AUDIO SINGLE 2-METER	kr.	4.950,00
CA1M	UNBALANCED AUDIO PAIR 1-METER	kr.	5.940,00
CA2M	UNBALANCED AUDIO PAIR 2-METER	kr.	6.930,00
CDA1M	COAX DIGITAL SINGLE 1-METER	kr.	4.455,00
CDA2M	COAX DIGITAL SINGLE 2-METER	kr.	5.445,00
CC1M	CONTROL SINGLE 1-METER	kr.	643,50
CC2M	CONTROL SINGLE 2-METER	kr.	742,50
CS2M	SPEAKER SINGLE 2-METER	kr.	10.890,00
СЅЗМ	SPEAKER SINGLE 3-METER	kr.	14.355,00

Confidential: This document contains copyrighted and trademarked information and pricing that is proprietary to McIntosh Laboratory, Inc.

Changes:

Prices models terms and conditions are subject to change without notice. The continuous improvement of its prodouct is the policy of Mcintosh Laboratory, Inc who reserves the right ot improve design or adjust the price without notice

PS AUDIO SCANDINAVIA

Der tages forbehold for tryk- og tastefejl, prisændringer og udsolgte varer.