







McIntosh[®]









LEGENDARY PERFORMANCE™

PS Audio
Scandinavia






POWER AMPS

Unit	Description	MSRP	DKI
MC2KW 	<ul style="list-style-type: none"> • 1 x 2000 Watts • Reference Series • Quad-Balanced Design • Separate Positive & Negative Amplifiers • 3 Full Sets of Terminals for Tri-Wiring @ 8, 4 & 2 Ohms • Silent Convection Cooling • Safe Operation to Below 2 Ohms 	kr.	405.000,00
MC1.25KW 	<p>NEW • 1 x 1200 Watts • Redesigned from top to bottom • Autoformer for 2, 4 & 8 Ohms • Exclusive McIntosh Power Assurance System • Direct LED Backlighting • 50% increase in filter capacity from previous model • McIntosh Monogrammed Heatsinks™ • Updated power transformer, internal wiring, circuit components and industrial design • Power management system • Power Guard®</p> <ul style="list-style-type: none"> • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	kr.	125.000,00
MC611 	<p>NEW • 1 x 600 Watts • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Direct LED Backlighting • 2x filter capacity from previous model results in 55% increase in dynamic headroom from 1.8dB to 2.8dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Updated internal wiring, circuit components and industrial design • Power Guard®</p> <ul style="list-style-type: none"> • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	kr.	75.000,00
MC301 	<ul style="list-style-type: none"> • 1 x 300 Watts • Quad-Balanced Design • Slim Chassis Design • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Power Guard to Prevent Clipping • ThermalTrak™ Output Transistors • Patented McIntosh Speaker Binding Posts 	kr.	55.000,00
MC2301 	<ul style="list-style-type: none"> • 1 x 300 watts • Balanced Unity-Coupled vacuum Tube Design • Peak Responding Wattmeter • Two Balanced Inputs/Outputs • Remote Power Control with Meter Light Control • Large Gold Plated Five-Way Binding Posts • ½" Thick Glass Front Panel with Tube View 	kr.	125.000,00
MC462 	<p>NEW • 2 x 450 Watts • Output Autoformers for 2, 4 & 8 Ohms • Nearly 2x filter capacity from previous model results in 66% increase in dynamic headroom from 1.8dB to 3.0dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Direct LED Backlighting • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts</p>	kr.	90.000,00


POWER AMPS

Unit	Description	MSRP
MC312 	NEW • 2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 2x filter capacity from previous model results in 27% increase in dynamic headroom from 1.8dB to 2.3dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Direct LED Backlighting • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts	kr. 70.000,00
MC302 	DISCONTINUED Availability subject to stock on hand	kr. 70.000,00
MC152 	<ul style="list-style-type: none"> • 2 x 150 Watts • Slim Chassis Design • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Power Guard to Prevent Clipping • ThermalTrak™ Output Transistors • Patented McIntosh Speaker Binding Posts 	kr. 50.000,00
MC275 	<ul style="list-style-type: none"> •Version VI Model• Same feature set as MC275LE but with polished stainless chassis •2 X 75 Watts •Outputs for 4, 8, 16 Ohms •Sentry Monitor Protection •Unique Tube Illumination to Indicate Operational Status •Front Apron Power Switch •Stereo/Mono Switch •Patented McIntosh Speaker Binding Posts •Power Control to Enable Remote On/Off with McIntosh Preamplifiers 	kr. 60.000,00
MC303 	<ul style="list-style-type: none"> •3 x 300 Watts •Output Autoformers •Peak Responding Wattmeters • LED Fiber-Optic Illumination •Exclusive McIntosh Power Assurance System •60 Amps Output Current •Large Gold Plated Five-Way Binding Posts 	kr. 115.000,00
MC205 	<ul style="list-style-type: none"> •3 x 200 Watts •Two-Zone Operation •DPM Circuit Design Ensures Full Power at 4 or 8 Ohms •Peak Responding Wattmeters •LED Fiber-Optic Illumination •Exclusive McIntosh Power Assurance System •Remote Power Control Trigger •Multi-Way Speaker Binding Posts 	kr. 75.000,00
MC207 	<ul style="list-style-type: none"> •7 x 200 Watts •Two-Zone Operation •DPM Circuit Design Ensures Full Power at 4 or 8 Ohms •Peak Responding Wattmeters •LED Fiber-Optic Illumination •Exclusive McIntosh Power Assurance System •Remote Power Control Trigger •Multi-Way Speaker Binding Posts 	kr. 95.000,00
MC8207 	<ul style="list-style-type: none"> •7 x 200 Watts •Two-Zone Operation •DPM Circuit Design Ensures Full Power at 4 or 8 Ohms •Theater-Friendly LED Meters •LED Fiber-Optic Panel Illumination •Exclusive McIntosh Power Assurance System •Remote Power Control Trigger •Multi-Way Speaker Binding Posts 	kr. 65.000,00




INTEGRATED AMPLIFIERS

Unit	Description	MSRP
MA9000 	<ul style="list-style-type: none"> • 2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 2 High-Level Balanced Inputs • MC & MM Phono Inputs (both adjustable loading) • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 8-Band Equalizer • Premium gold-plated solid brass analog connectors • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Solid Cinch™ speaker binding posts • Upgraded audio components 	kr. 110.000,00
MA8900 	<ul style="list-style-type: none"> • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 5-Band Equalizer • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	kr. 80.000,00
MA5300 	<p>NEW • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • 4 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • DA1 Digital Audio Module w/ 6 inputs • DSD256 & DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • McIntosh Monogrammed Heatsinks™ • ¼" High Drive Headphone Jack w/ Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Bass & Treble tone controls</p>	kr. 55.000,00
MA252 	<p>NEW • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • Hybrid: Vacuum Tube preamp + solid state power amp • (2) 12AX7a & (2) 12AT7 vacuum tubes in preamp • Direct couple amp • 2 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • Bass & Treble tone controls • McIntosh Monogrammed Heatsinks™ • ¼" High Drive Headphone Jack • Power Guard® • Sentry Monitor™ • Power Control • Retro styling • Die cast aluminum name badge on each side • Remote control</p>	kr. 40.000,00
MA7200 	<p>NEW • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard®</p> <ul style="list-style-type: none"> • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	RING FOR PRIS







RECEIVERS

Unit	Description	MSRP
MAC7200 	<p>NEW • 2 x 200 Watts • Built in AM/FM Tuner • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls</p> <ul style="list-style-type: none"> • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	kr. 75.000,00


HEADPHONE AMPLIFIERS

Unit	Description	MSRP
<p>MHA150</p> 	<ul style="list-style-type: none"> • Headphone Amplifier • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD®) images quality recordings like conventional speakers • Power Guard • 50 Watt stereo speaker terminals • Compact size for placement flexibility • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport 	<p>kr. 55.000,00</p>
<p>MHA100</p> 	<p>DISCONTINUED Availability subject to stock on hand</p>	<p>kr. 45.000,00</p>
<p>MHA50</p> 	<p>NEW • Portable Decoding Amplifier • Comparably sized to smartphones • Inputs: wired inputs for iOS devices & Android devices with USB On-The-Go technology; Mac® & Windows® PCs; Bluetooth® 4.1 with aptX™ • 3.5mm gold plated headphone jack • High-performance DAC supports 32-bit/192kHz hi-res audio, up to DSD128 & DXD384 files & asynchronous USB audio • Up to 6 hours of playback on a single battery charge • 2 gain settings drive 8-600 Ohms • Headphone Crossfeed Director (HXD®) • Includes: leather case; 4 USB adapter cables; wall mount charger</p>	<p>kr. 7.000,00</p>



AUDIO PREAMP CONTROL CENTERS

Unit	Description	MSRP
C1100C 	<ul style="list-style-type: none"> • Controller for Reference series multi-chassis C1100T Vacuum Tube Preamp • Keeps control & power sections separate from the audio section • Left & right channels are electrically & mechanically isolated from each other to allow true dual mono operation • Connected to C1100T by specially designed, shielded & high performance umbilical cables • Requires use of C1100T 	kr. 70.000,00
C1100T 	<ul style="list-style-type: none"> • Vacuum Tube Preamp to be used with C1100C Controller • High level inputs have the lowest noise of any McIntosh preamplifier ever produced • 6 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 12 vacuum tubes • 2 Balanced (XLR) Outputs • 2 Unbalanced Outputs • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • Requires use of C1100C 	kr. 70.000,00
D1100 	<ul style="list-style-type: none"> • Reference Level Digital Preamplifier with our most advanced DAC • 8-channel, 32-bit DAC is used in Quad Balanced mode • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • 9 Inputs: 3 coax, 3 optical, 1 each MCT (for SACD playback from MCT450 Transport), AES/EBU & USB • 3 sets of Balanced and Unbalanced stereo outputs (1 set fixed volume, 2 sets variable) • 1 Headphone Jack (¼") with Headphone Crossfeed Director (HXD®) • Audio channels & power supplies are electrically isolated from each other for dual mono operation • Can be used by itself or in tandem with analog C1100 Vacuum Tube Preamp • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis • RS232 	kr. 75.000,00
C2600 	<ul style="list-style-type: none"> • Vacuum Tube Preamplifier • 3 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced (XLR) Outputs • 3 Unbalanced Outputs • 3 Optical & 2 Coax Inputs at 24-bit/192kHz • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • Output Meters 	kr. 75.000,00
C47 	<ul style="list-style-type: none"> • 2 Balanced (XLR) Inputs • 2 Unbalanced Inputs • MC & MM Phono Inputs • 2 Balanced (XLR) Outputs • 2 Unbalanced Outputs • 2 Optical & 1 Coax Inputs at 24-bit/192kHz • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) 	kr. 45.000,00
C52 	<ul style="list-style-type: none"> • 3 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced (XLR) Outputs • 3 Unbalanced Outputs • 3 Optical & 2 Coax Inputs at 24-bit/192kHz • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • 8 Band Equalizer • Output Meters 	kr. 75.000,00


AUDIO PREAMP CONTROL CENTERS

Unit	Description	MSRP
D150 	<ul style="list-style-type: none"> • Digital Stereo Preamplifier • Supports DSD64, DSD128, DXD 352.8kHz and DXD 384kHz • 6 Digital Inputs: 2 Coaxial, 2 Optical, 1 USB and 1 DIN • 1 Set Each: Balanced & Unbalanced Fixed and Balanced & Unbalanced Variable Audio Outputs • Power and Data Control Ports • Compact Form Factor of just under 4" in Height • 8 Channel, 32-bit, 500kHz D/A Converter with Wide Dynamic Range and Extremely Low Distortion 	kr. 35.000,00



PHONO PREAMPLIFIERS

Unit	Description	MSRP
MP1100 	<ul style="list-style-type: none"> • Dedicated Vacuum Tube Phono Preamplifier • Fully Balanced Vacuum Tube Phono Stage • Four 12AX7A Vacuum Tubes (2 tubes per channel) • 3 sets of RCA Phono Inputs (XLR connectors available on 1 of the inputs) • 4 Pre-Programmed & 5 Programmable Profiles • 8 Capacitance & 7 Resistance Settings • 5 Analog Equalization Curves • 2 Analog Noise Filters • Adjustable Gain • 1 pair of Balanced & Unbalanced Line Inputs & Fixed Outputs • Coax, Optical & USB Digital Outputs • Rip to computer via USB • Digital Output Clipping Indicator • Mono setting • Dual Mono design • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis 	kr. 85.000,00
MP100 	<ul style="list-style-type: none"> • Dedicated Phono Preamplifier • Adjustable Moving Coil & Moving Magnet inputs (6 settings each) • Balanced & Unbalanced Analog Outputs • Coax, Optical and USB Digital Outputs • Rip to computer via USB • Digital output clipping indicator • Mono switch • Narrow chassis 	kr. 20.000,00





AUDIO VIDEO CONTROL CENTER/ROOM CORRECTION SYSTEM

Unit	Description	MSRP
MX160 	<ul style="list-style-type: none"> • 16 Channel A/V Processor used in 11.1 (aka 7.1.4) w/ 4 AUX channels (all 16 are balanced) • Supports Dolby Atmos, Auro-3D & DTS-HD Master Audio with planned upgrade for DTS:X • Supports 4K Ultra HD native sources plus upscaling of lower resolutions • 3D video supported • Built in RoomPerfect room correction • 8 HDMI inputs & 4 HDMI outputs (all HDCP 2.2) • HDBaseT output • 2 sets of stereo balanced, 4 sets of stereo unbalanced, dedicated phono & 7.1 multi-channel unbalanced inputs • 4 optical, 3 coax & 1 XLR digital audio inputs • Supports DSD64, DSD128, DXD 352.8kHz and DXD 384kHz via USB • Supports 5 zones with independent audio & video plus additional audio only zone 	kr. 145.000,00







AUDIO VIDEO CONTROL CENTER/ROOM CORRECTION SYSTEM

Unit	Description	MSRP
MX122 	<ul style="list-style-type: none"> • 13 Channel A/V Processor used in 11.2 (aka 7.2.4) • Dolby Atmos with planned upgrades for DTS:X & Auro-3D • Supports 4K Ultra HD native sources plus upscaling • 3D video supported • HDMI: 7 inputs & 3 outputs (all HDCP 2.2, HDR, 4K Ultra HD at 50/60Hz, 4:4:4 color, Rec. 2020) • Inputs: 1 stereo balanced • 7 stereo unbalanced + 1 dedicated phono • 7.1 multi-channel unbalanced • 3 component • 4 composite • 2 optical & 2 coax digital audio inputs • DSD64 via USB • Audyssey MultEQ XT32 room correction • Bluetooth & Airplay • Interfaces to Pandora, SiriusXM & Spotify + vTuner • Stereo audio & video for Zone 2 + stereo audio for Zone 3 • 9 band equalizer 	kr. 75.000,00
MEN220 	<ul style="list-style-type: none"> • RoomPerfect Room Correction • Custom EQ Application (that runs on any Windows PC) • 2-Way Crossover for true bi-amping of any loudspeaker • Audio Inputs: 2 Single-Ended & 2 Balanced • Audio Outputs: • High-Pass: 2 Single-Ended & 2 Balanced 	kr. 55.000,00




SOURCE COMPONENTS

Unit	Description	MSRP
MCD600 	<p>NEW • 2-Channel SACD/CD Player • Premium 8-Channel, 32-bit Quad Balanced PCM/DSD DAC • Both Stereo Balanced & Unbalanced Fixed & Variable Analog Outputs • Plays SACD, CD, CD-R/RW & DVD-R • Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • Headphone Amp</p>	kr. 75.000,00
MCD550 	<p>DISCONTINUED Availability subject to stock on hand</p>	kr. 65.000,00
MCD350 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Player • 2-Channel, 32-bit/192kHz balanced PCM/DSD DAC (decodes PCM signals from CDs; DSD signals from SACDs) • Fixed analog stereo balanced and unbalanced outputs • Digital coax and optical outputs • 2x read speed for better reading of damaged CDs and CD-R/RWs 	kr. 55.000,00
MCT500 	<p>NEW • 2-Channel SACD/CD Transport • Digital balanced, coax, optical & MCT outputs • Unique MCT output connects to select McIntosh models with a MCT input for playback of SACD high definition audio • Plays SACD, CD, CD-R/RW & DVD-R • Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • 2x read speed</p>	kr. 50.000,00




SOURCE COMPONENTS

Unit	Description	MSRP
MCT80 	NEW • 2-Channel SACD/CD Transport sized to match MXA80 Integrated Audio System • Digital coaxial, optical and MCT (DIN) outputs • Unique MCT output connects to select McIntosh models with a MCT input for the purist possible sound quality • Plays SACD, CD, CD-R/RW & user generated DVD or CD Data Discs • Die-cast aluminum tray • Advanced digital servo for faster, quieter & accurate operation • 2x read speed for better reading of damaged CDs & CD-R/RWs	kr. 40.000,00
MVP901 	• Universal Blu-ray DVD/CD Player • Upsamples to 4K Ultra HD • 3D Video • Built in decoding of Dolby True HD & DTS-HD Master Audio + legacy formats • Passes object-based 3D audio formats Dolby Atmos, DTS:X & Auro-3D to compatible processor • Fast Disc Loading • Quad Balanced 32-bit/192kHz DAC for stereo playback of CD/SACD/DVD-Audio discs • BD-Live & File Sharing Over Home Network	kr. 60.000,00
MR87 	• AM/FM/HD Radio Tuner with Multi-Casting • XM-ready • Illuminated Analog Dial and 2-Line Multi-Function Fluorescent Display • Smooth-Acting, Weighted Tuning Mechanism with Animated Dial Pointer • Dual-Differential Remote AM Antenna • External AM and FM Antenna Inputs • 60 Station Presets (20 per band) • Balanced and Single-ended Analog Output • Coaxial and Optical Digital Audio Output	kr. 50.000,00
MT10 	• Belt-Drive Turntable • Dural Aluminum Tone Arm • Weight-Matched Moving Coil Cartridge Included • Precision AC Motor • Magnetic Spindle Bearing • Strobe Speed Control • Illuminated Speed Meter • Multi-Layered Damped Chassis	kr. 110.000,00
MT5 	• Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Magnetic Spindle Bearing • Multi-Layered Damped Chassis • Includes Plexi Dustcover	kr. 70.000,00
MT2 	• Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • Plays 33-1/3 and 45 rpm records • High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Resonance optimized and highly compressed wood base with black lacquer finish • Includes Plexi Dustcover	kr. 45.000,00





INTEGRATED AUDIO SYSTEMS

Unit	Description	MSRP
 <p>McAire</p>	<ul style="list-style-type: none"> • Built in AirPlay® allows wireless streaming of music via Wi-Fi network from Mac or PC based iTunes® library, iPad®, iPhone® or iPod touch® • USB docking is available for all day playback and charging • Computers and TVs may be quickly connected for full range, high fidelity sound <ul style="list-style-type: none"> • Two 4" woofers, two 2" midranges, two 3/4" tweeters • Delivers the legendary McIntosh look and sound quality in a compact size 	<p>kr. 30.000,00</p>
 <p>MXA70</p>	<p><u>DISCONTINUED Availability subject to stock on hand</u></p>	<p>kr. 60.000,00</p>
 <p>MXA80</p>	<ul style="list-style-type: none"> • Compact System • 2 x 50 Watts • Pair of specially designed 8 Ohm 2-way speakers • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD) images high quality recordings like conventional speakers <ul style="list-style-type: none"> • Power Guard to Prevent Clipping and Speaker Damage • 5 Step Bass Boost Control • Polished Stainless Steel Chassis 	<p>kr. 60.000,00</p>






MEDIA STREAMERS

Unit	Description	MSRP
 <p>MB50</p>	<p>*NOT AVAILABLE IN ALL TERRITORIES • Streaming audio player featuring DTS Play-Fi technology • Connects to existing Wi-Fi to turn traditional audio system into a wireless audio system • Free Apple & Android app to stream music library stored on mobile device • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Analog & digital inputs for mini-preamp functionality • Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • Narrow chassis</p>	<p>kr. 20.000,00</p>
 <p>MS500</p>	<p>NEW • Seamlessly integrates internet based streaming music & locally stored digital music into one comprehensive device • Up to 24 bit/192kHz output • Built-in interfaces to streaming services such as Deezer, Murfie, Pandora®, Rhapsody®, SiriusXM®, Slacker, Spotify® & TIDAL (list subject to change) • Ultra-quiet thanks to solid state drive & fanless processor with no noisy cooling fans • Synchronizes content stored on networked computers so it is readily playable • Secure back to Amazon Cloud Drive, Apple iCloud or Google Drive • Linux based OS • 3 USB ports to connect external drives • 1 additional independent audio zone can be created when using an external DAC</p>	<p>kr. 60.000,00</p>
 <p>MB100</p>	<p><u>DISCONTINUED Availability subject to stock on hand</u></p>	<p>kr. 60.000,00</p>



LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	MSRP
XRT2.1KL 	<p>NEW • Reference Series Dual-Column 4-Way Ported Line-Source • 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3/4" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Left speaker only (see XRT2.1KR for matching right speaker)</p>	<p>kr. 650.000,00</p>
XRT2.1KR 	<p>NEW • Reference Series Dual-Column 4-Way Ported Line-Source • 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3/4" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Right speaker only (see XRT2.1KL for matching left speaker)</p>	<p>kr. 650.000,00</p>
XRT1.1KL 	<p>NEW • Dual-Column 4-Way Ported Line Array • 70 Total Drivers • 4 x 6.5" Woofers • 2 x 6.5" Low Frequency Midranges • 24 x 2" Upper Frequency Midranges • 40 x 3/4" Tweeters • 16 Hz - 45 kHz Response • 89dB SPL • 1,200 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 5.9' (1.8 meters) tall • Piano Black finish • Left speaker only (see XRT1.1KR for matching right speaker)</p>	<p>kr. 300.000,00</p>
XRT1.1KR 	<p>NEW • Dual-Column 4-Way Ported Line Array • 70 Total Drivers • 4 x 6.5" Woofers • 2 x 6.5" Low Frequency Midranges • 24 x 2" Upper Frequency Midranges • 40 x 3/4" Tweeters • 16 Hz - 45 kHz Response • 89dB SPL • 1,200 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 5.9' (1.8 meters) tall • Piano Black finish • Right speaker only (see XRT1.1KL for matching left speaker)</p>	<p>kr. 300.000,00</p>






LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

<p>CK200</p>	<p align="center">In Wall Mounting Kit for XCS200</p>	<p align="right">kr. 7.000,00</p>
<p>RS100</p> 	<p>*NOT AVAILABLE IN ALL TERRITORIES* Wireless speaker featuring DTS Play-Fi technology • Start with 1 then add more to build system • Up to 16 can be added to a Wi-Fi network • Connect to existing Wi-Fi & then stream music library from mobile device via free Apple & Android app • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • AUX input for non-streaming use • Subwoofer output</p>	<p align="right">kr. 10.000,00</p>
<p>XR50</p> 	<ul style="list-style-type: none"> • True 3-Way Compact Bookshelf Speaker • 40 Hz - 45 kHz Frequency Response • 1 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 1 x 3/4" Titanium Super Tweeter • 300-Watt Music Power-Handling • Patented McIntosh Binding Posts • Front-Panel McIntosh Logo Illumination using Power Control • Premium cabinet finishes include Red Walnut, Gloss Black 	<p align="right">kr. 20.000,00</p>
<p>XR100</p> 	<ul style="list-style-type: none"> • True 4-way Floor-Standing Tower Speaker • 30 Hz - 45 kHz Frequency Response • 4 x 6" LDHP Woofers • 8 x 2" Titanium Midrange • 2 x 2" Titanium Tweeters • 1 x 3/4" Titanium Super Tweeter • Dual Sets of Patented McIntosh Binding Posts Enable Bi-Wire or Bi-Amplification • 600-Watt Music Power Handling • Front-Panel McIntosh Logo Illumination Using Power Control • Premium Cabinet Finishes Include Red Walnut, Gloss Black 	<p align="right">kr. 50.000,00</p>
<p>LCR80</p> 	<ul style="list-style-type: none"> • True 3-Way Center-Channel Speaker • 80Hz to 45 kHz Frequency Response • 2 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 1 x 3/4" Titanium Super Tweeter • 300-Watt Music Power-Handling • Voiced to Match XR50 & XR100 • Patented McIntosh Binding Posts • Premium Cabinet Finishes include Red Walnut, Gloss Black (Pear Maple Discontinued) 	<p align="right">kr. 25.000,00</p>
<p>HT30-IW</p> 	<ul style="list-style-type: none"> • IN-Wall THX Licensed Dipole Surround Speaker • 200 Watts Max Continuous Power • 2 x 5" Polypropylene Woofers • 2 x 1" Aluminum Dome Tweeters • Paintable Frame & Metal Grill <p align="center">SOLD IN PAIRS</p>	<p align="right">kr. 28.000,00</p>

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	MSRP
HT30-OW 	<ul style="list-style-type: none"> • ON-Wall THX Licensed Dipole Surround Speaker • 200 Watts Max Continuous Power • 2 x 5" Polypropylene Woofers • 2 x 1" Aluminum Dome Tweeters • Paintable Frame & Metal Grill <p align="center">SOLD IN PAIRS</p>	kr. 28.000,00
RK100	New Construction Rough-In Kit for CS100	kr. 450,00
WS350 	<ul style="list-style-type: none"> • IN-Wall 3-Way Speaker • 200 Watts Max Continuous Power Handling • 5-Tweeter Bessel Array • One 8" Woofer • One 4" Midrange • Five 1" Dome Tweeters • Deep-Drawn Sealed Aluminum Enclosure • Paintable Frame & Metal Grille 	kr. 22.000,00
RK320	RETURNED TO ACTIVE PRODUCTION	kr. 450,00

ACCESSORIES

Unit	Description	MSRP
MPC1500 	<ul style="list-style-type: none"> • AC Isolation Transformer & AC Switching Hub • 12 Rear Panel AC Outlets with Programmable Power Control Options • Front and Rear Panel LED Status Indicators • Front Panel Back-Lit Meters Display Line Voltage & Amperage 	kr. 55.000,00
MC CLOCK 	The McIntosh Clock boast our trademak glass front pannel and two of our blue meters , One to show the hour and the other to show minutes.	kr. 18.000,00
LB100 	Unmistakably McIntosh. The LB100 Light Box proudly displays the "Handcrafted In The USA Since 1949" statement as a badge of honor. A must for every McIntosh owner. Approximately the size of a McIntosh CD player. Includes Power Control for seamless on/off with other McIntosh components.	kr. 15.000,00
BLI-23 (pair)	Balanced Line Integrator, 2 XLR Inputs & 3 XLR Outputs	kr. 3.000,00
MCBOOK 	"For the Love of Music" -- The History of McIntosh	kr. 1.500,00
TM3 Tuner Module 	<ul style="list-style-type: none"> • AM/FM/HD Radio Tuner Module for use with MA6600 Integrated Amplifier • Includes Dual-Differential Remote AM Antenna • External AM and FM antenna inputs 	kr. 8.000,00

AUDIO CABLES

Unit	Description	MSRP
CBA1M	BALANCED AUDIO SINGLE 1-METER	kr. 4.000,00
CBA2M	BALANCED AUDIO SINGLE 2-METER	kr. 5.000,00
CA1M	UNBALANCED AUDIO PAIR 1-METER	kr. 6.000,00
CA2M	UNBALANCED AUDIO PAIR 2-METER	kr. 7.000,00
CDA1M	COAX DIGITAL SINGLE 1-METER	kr. 4.500,00
CDA2M	COAX DIGITAL SINGLE 2-METER	kr. 5.500,00
CC1M	CONTROL SINGLE 1-METER	kr. 6.500,00
CC2M	CONTROL SINGLE 2-METER	kr. 750,00
CS2M	SPEAKER SINGLE 2-METER	kr. 11.000,00
CS3M	SPEAKER SINGLE 3-METER	kr. 14.500,00

PS AUDIO SCANDINAVIA

Der tages forbehold for tryk- og tastefejl, prisændringer og udsolgte varer.