










Prisliste 2020

McIntosh®








LEGENDARY PERFORMANCE™

PS Audio
Scandinavia







POWER AMPS

Unit	Description	DKK
MC2KW 	<ul style="list-style-type: none"> • 1 x 2000 Watts • Reference Series • Quad-Balanced Design • Separate Positive & Negative Amplifiers • 3 Full Sets of Terminals for Tri-Wiring @ 8, 4 & 2 Ohms • Silent Convection Cooling • Safe Operation to Below 2 Ohms 	399.000,00 kr.
MC901 	NEW • 1 x 300 Watts vacuum tube and 1 x 600 Watts solid state • The ultimate solution for bi-amping loudspeakers: 300 Watt vacuum tube amplifier & 600 Watt solid state amplifier on one chassis • Vacuum tube section powers mid & upper drivers • Solid state section drives woofers • Full power into 2, 4 or 8 Ohms via Unity Coupled Circuit output transformer for tubes & Autoformer™ for solid state • Adjustable crossover filters • Power Guard® for solid state • New Power Guard Screen Grid Sensor™ (SGS) for tubes • Sentry Monitor™ • Quad-Balanced Design • New DualView™ Power Output Meter • McIntosh Monogrammed Heatsinks™ • Power Control • Solid Cinch™ speaker binding posts	174.995,00 kr.
MC1.25KW 	<ul style="list-style-type: none"> • 1 x 1200 Watts • Redesigned from top to bottom • Autoformer for 2, 4 & 8 Ohms • Exclusive McIntosh Power Assurance System • Direct LED Backlighting • 50% increase in filter capacity from previous model • McIntosh Monogrammed Heatsinks™ • Updated power transformer, internal wiring, circuit components and industrial design • Power management system • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	124.995,00 kr.
MC611 	<ul style="list-style-type: none"> • 1 x 600 Watts • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Direct LED Backlighting • 2x filter capacity from previous model results in 55% increase in dynamic headroom from 1.8dB to 2.8dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	74.995,00 kr.
MC2301 	<ul style="list-style-type: none"> • 1 x 500 Watts • Balanced Unity-Coupled Vacuum Tube Design • Peak Responding Wattmeter • Two Balanced Inputs/Outputs • Remote Power Control with Meter Light Control • Large Gold Plated Five-Way Binding Posts • ½" Thick Glass Front Panel with Tube View 	124.995,00 kr.
MC462 	<ul style="list-style-type: none"> • 2 x 450 Watts • Output Autoformers for 2, 4 & 8 Ohms • Nearly 2x filter capacity from previous model results in 66% increase in dynamic headroom from 1.8dB to 3.0dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Direct LED Backlighting • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	89.995,00 kr.
MC312 	<ul style="list-style-type: none"> • 2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 2x filter capacity from previous model results in 27% increase in dynamic headroom from 1.8dB to 2.3dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Direct LED Backlighting • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts 	69.995,00 kr.
MC152 	<ul style="list-style-type: none"> • 2 x 150 Watts • Slim Chassis Design • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Power Guard to Prevent Clipping • ThermalTrak™ Output Transistors • Patented McIntosh Speaker Binding Posts 	49.995,00 kr.
MC275 	<ul style="list-style-type: none"> • Version VI Model • Same feature set as MC275LE but with polished stainless chassis • 2 X 75 Watts • Outputs for 4, 8, 16 Ohms • Sentry Monitor Protection • Unique Tube Illumination to Indicate Operational Status • Front Apron Power Switch • Stereo/Mono Switch • Patented McIntosh Speaker Binding Posts • Power Control to Enable Remote On/Off with McIntosh Preamplifiers 	59.995,00 kr.


POWER AMPS

Unit	Description	DKK
MC2152 	<ul style="list-style-type: none"> • 70th Anniversary Model with anniversary markings • 2 x 150 Watts • Unity Coupled Output Transformers for 2, 4 & 8 Ohms • (8) KT88, (4) 12AX7A and (4) 12AT7 vacuum tubes • Bead blasted black anodized aluminum chassis accentuated with matte finish carbon fiber side panels • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts 	149.995,00 kr.
MC303 	<ul style="list-style-type: none"> • 3 x 300 Watts • Output Autoformers • Peak Responding Wattmeters • LED Fiber-Optic Illumination • Exclusive McIntosh Power Assurance System • 60 Amps Output Current • Large Gold Plated Five-Way Binding Posts 	114.795,00 kr.
MC255 	<ul style="list-style-type: none"> • 250 Watts x 3 Channels; 200 Watts x 5 Channels • Designed for home theaters • TripleView™ Power Output Meter indicates the real time power reading of the 3 front channels • More than 100% increase in dynamic headroom • McIntosh Monogrammed Heatsinks™ and a specially wound toroidal isolation power transformer for low noise • Power Guard® • Sentry Monitor™ • Power Control • Standard gold-plated binding posts • 2 channels can power a separate zone • Direct LED Backlighting 	79.995,00 kr.
MC257 	<ul style="list-style-type: none"> • 250 Watts x 3 Channels; 200 Watts x 7 Channels • Designed for home theaters • TripleView™ Power Output Meter indicates the real time power reading of the 3 front channels • 94% increase in dynamic headroom • McIntosh Monogrammed Heatsinks™ and a specially wound toroidal isolation power transformer for low noise • Power Guard® • Sentry Monitor™ • Power Control • Standard gold-plated binding posts • 2 channels can power a separate zone • Direct LED Backlighting 	98.995,00 kr.
MC8207 	<ul style="list-style-type: none"> • 7 x 200 Watts • Two-Zone Operation • DPM Circuit Design Ensures Full Power at 4 or 8 Ohms • Theater-Friendly LED Meters • LED Fiber-Optic Panel Illumination • Exclusive McIntosh Power Assurance System • Remote Power Control Trigger • Multi-Way Speaker Binding Posts 	64.995,00 kr.
MI128 	<ul style="list-style-type: none"> • 8 x 120 Watts into 8 Ohms or 150 Watts into 4 Ohms • 8-channel Class D amplifier for custom install distributed audio, home theater or stereo listening • Installer-friendly physical dimensions • 2U rack mountable • Unbalanced inputs • 2-pole Phoenix style push-in speaker terminals • Volume controls for volume balancing • 2 digital audio inputs • Channel summing circuits for easy mono signal distribution • Loudspeaker Guard • Sentry Monitor™ • BUS input & outputs to easily distribute a stereo signal to multiple outputs and/or multiple amplifiers • Eco-friendly on/off signal sensing 	34.995,00 kr.
MI254 	<ul style="list-style-type: none"> • 4 x 250 Watts into 8 Ohms or 300 Watts into 4 Ohms • 4-channel Class D amplifier for custom install distributed audio, home theater or stereo listening • Installer-friendly physical dimensions • 2U rack mountable • McIntosh Watt Meters that display the summed power output of channels 1 + 2 and channels 3 + 4 • Balanced & unbalanced inputs • 5-way speaker binding posts • Loudspeaker Guard • Sentry Monitor™ • BUS input & outputs to easily distribute a stereo signal to multiple outputs and/or multiple amplifiers • Eco-friendly on/off signal sensing 	43.795,00 kr.



INTEGRATED AMPLIFIERS

Unit	Description	DKK
MA9000 	<ul style="list-style-type: none"> • 2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 2 High-Level Balanced Inputs • MC & MM Phono Inputs (both adjustable loading) • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 8-Band Equalizer • Premium gold-plated solid brass analog connectors • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Solid Cinch™ speaker binding posts • Upgraded audio components 	108.995,00 kr.
MA8900 	<ul style="list-style-type: none"> • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 5-Band Equalizer • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	79.995,00 kr.
MA5300 	<ul style="list-style-type: none"> • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • 4 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • DA1 Digital Audio Module w/ 6 inputs • DSD256 & DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • McIntosh Monogrammed Heatsinks™ • ¼" High Drive Headphone Jack w/ Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Bass & Treble tone controls 	53.795,00 kr.
MA352 	<ul style="list-style-type: none"> • 2 x 200 Watts into 8 Ohm or 320 Watts into 4 Ohm • Hybrid: Vacuum Tube preamp + solid state power amp • (2) 12AX7A & (2) 12AT7 vacuum tubes in preamp • Direct coupled amp • 3 Unbalanced & 2 Balanced Inputs • Moving Magnet Input • 5-Band tone control • McIntosh Monogrammed Heatsinks™ • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Retro styling • Die cast aluminum name badges • Remote control 	64.995,00 kr.
MA252 	<ul style="list-style-type: none"> • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • Hybrid: Vacuum Tube preamp + solid state power amp • (2) 12AX7a & (2) 12AT7 vacuum tubes in preamp • Direct couple amp • 2 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • Bass & Treble tone controls • McIntosh Monogrammed Heatsinks™ • ¼" High Drive Headphone Jack • Power Guard® • Sentry Monitor™ • Power Control • Retro styling • Die cast aluminum name badge on each side • Remote control 	39.795,00 kr.
MA7200 	<ul style="list-style-type: none"> • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	59.850,00 kr.




RECEIVERS

Unit	Description	DKK
MAC7200 	<ul style="list-style-type: none"> • 2 x 200 Watts • Built in AM/FM Tuner • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	73.995,00 kr.





HEADPHONE AMPLIFIERS

Unit	Description	DKK
MHA150 	<ul style="list-style-type: none"> • Headphone Amplifier • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD®) images quality recordings like conventional speakers • Power Guard • 50 Watt stereo speaker terminals • Compact size for placement flexibility • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport 	48.550,00 kr.
MHA50 	<ul style="list-style-type: none"> • Portable Decoding Amplifier • Comparably sized to smartphones • Inputs: wired inputs for iOS devices & Android devices with USB On-The-Go technology; Mac® & Windows® PCs; Bluetooth® 4.1 with aptX™ • 3.5mm gold plated headphone jack • High-performance DAC supports 32-bit/192kHz hi-res audio, up to DSD128 & DXD384 files & asynchronous USB audio • Up to 6 hours of playback on a single battery charge • 2 gain settings drive 8-600 Ohms • Headphone Crossfeed Director (HXD®) • Includes: leather case; 4 USB adapter cables; wall mount charger 	6.895,00 kr.



AUDIO PREAMP CONTROL CENTERS

Unit	Description	DKK
C1100C 	<ul style="list-style-type: none"> • Controller for Reference series multi-chassis C1100T Vacuum Tube Preamp • Keeps control & power sections separate from the audio section • Left & right channels are electrically & mechanically isolated from each other to allow true dual mono operation • Connected to C1100T by specially designed, shielded & high performance umbilical cables • Requires use of C1100T 	68.785,00 kr.
C1100T 	<ul style="list-style-type: none"> • Vacuum Tube Preamp to be used with C1100C Controller • High level inputs have the lowest noise of any McIntosh preamplifier ever produced • 6 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 12 vacuum tubes • 2 Balanced (XLR) Outputs • 2 Unbalanced Outputs • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • Requires use of C1100C 	68.995,00 kr.
D1100 	<ul style="list-style-type: none"> • Reference Level Digital Preamplifier with our most advanced DAC • 8-channel, 32-bit DAC is used in Quad Balanced mode • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • 9 Inputs: 3 coax, 3 optical, 1 each MCT (for SACD playback from MCT450 Transport), AES/EBU & USB • 3 sets of Balanced and Unbalanced stereo outputs (1 set fixed volume, 2 sets variable) • 1 Headphone Jack (¼") with Headphone Crossfeed Director (HXD®) • Audio channels & power supplies are electrically isolated from each other for dual mono operation • Can be used by itself or in tandem with analog C1100 Vacuum Tube Preamp • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis • RS232 	74.995,00 kr.




AUDIO PREAMP CONTROL CENTERS

Unit	Description	DKK
C70 	<ul style="list-style-type: none"> • 70th Anniversary Model with anniversary markings • Vacuum Tube Stereo Preamplifier • (5) 12AX7A and (1) 12AT7 vacuum tubes • All analog design and a retro look • 2 balanced, 3 unbalanced, 1 Moving Coil, 1 Moving Magnet input (phono inputs are adjustable) • 2 balanced, 2 unbalanced outputs • Bass and treble tone controls • High Drive headphone amplifier with Headphone Crossfeed Director (HXD®) technology • Power Control 	68.785,00 kr.
C2700 	<ul style="list-style-type: none"> • Vacuum Tube Preamplifier • 3 Balanced Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced Outputs • 4 Unbalanced Outputs • DA2 Digital Audio Module with 7 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT, 1 HDMI (ARC only) • DSD512 and DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC used in Quad Balanced mode • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD®) • Output Meters 	79.995,00 kr.
C53 	<ul style="list-style-type: none"> • 3 Balanced Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced Outputs • 4 Unbalanced Outputs • DA2 Digital Audio Module with 7 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT, 1 HDMI (ARC only) • DSD512 and DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC used in Quad Balanced mode • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD®) • 8 Band Equalizer • Output Meters 	79.995,00 kr.
C49 	<ul style="list-style-type: none"> • 2 Balanced Inputs • 3 Unbalanced Inputs • MC & MM Phono Inputs • 2 Balanced Outputs • 3 Unbalanced Outputs • DA1 Digital Audio Module with 6 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD®) 	48.550,00 kr.











PHONO PREAMPLIFIERS

Unit	Description	DKK
MP1100 	<ul style="list-style-type: none"> • Dedicated Vacuum Tube Phono Preamplifier • Fully Balanced Vacuum Tube Phono Stage • Four 12AX7A Vacuum Tubes (2 tubes per channel) • 3 sets of RCA Phono Inputs (XLR connectors available on 1 of the inputs) • 4 Pre-Programmed & 5 Programmable Profiles • 8 Capacitance & 7 Resistance Settings • 5 Analog Equalization Curves • 2 Analog Noise Filters • Adjustable Gain • 1 pair of Balanced & Unbalanced Line Inputs & Fixed Outputs • Coax, Optical & USB Digital Outputs • Rip to computer via USB • Digital Output Clipping Indicator • Mono setting • Dual Mono design • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis 	83.995,00 kr.
MP100 	<ul style="list-style-type: none"> • Dedicated Phono Preamplifier • Adjustable Moving Coil & Moving Magnet inputs (6 settings each) • Balanced & Unbalanced Analog Outputs • Coax, Optical and USB Digital Outputs • Rip to computer via USB • Digital output clipping indicator • Mono switch • Narrow chassis 	18.995,00 kr.





AUDIO VIDEO CONTROL CENTER/ROOM CORRECTION SYSTEM

Unit	Description	DKK
MX170 	<ul style="list-style-type: none"> • 16 Channel A/V Processor used in 15.1 (all 16 are balanced) • Supports Dolby Atmos, DTS:X & Auro-3D • 8 HDMI inputs & 4 HDMI outputs • All HDMI ports are HDCP 2.2 w/18Gbps of bandwidth • Supports 4K Ultra HD native sources and full 4:4:4 color spacing • Supports Dolby Vision™, HDR10 and HLG • eARC on 1 HDMI output • 3D video supported • RoomPerfect room correction • HDBaseT output • 2 sets of stereo balanced, 4 sets of stereo unbalanced, dedicated phono & 7.1 multi-channel unbalanced inputs • 4 optical, 3 coaxial and 1 USB that each accept up to 24-bit/192kHz • Easy to use and robust setup program allows for great customization and optimization 	153.785,00 kr.
MX123 	<ul style="list-style-type: none"> • 15 Channel A/V Processor used in 13.2 • Supports Dolby Atmos, DTS:X & Auro-3D • Supports 4K Ultra HD native sources plus upscaling • 3D video supported • HDMI: 7 inputs & 3 outputs (all HDCP 2.3, 4K Ultra HD at 50/60Hz, 4:4:4 color, Rec. 2020) • Supports Dolby Vision™, HDR10, HLG & IMAX Enhanced • eARC on 1 HDMI output • Inputs: 1 stereo balanced; 7 stereo unbalanced + 1 dedicated phono; 7.1 multi-channel unbalanced; 3 component; 4 composite; 2 optical & 2 coax digital audio • DSD128 and ALAC 192kHz • Audyssey MultEQ XT32 room correction • Airplay 2, Bluetooth, Spotify Connect, TuneIn • Zonable • 9 band equalizer + bass and treble • Dual band WiFi 	78.995,00 kr.
MEN220 	<ul style="list-style-type: none"> • RoomPerfect Room Correction • Custom EQ Application (that runs on any Windows PC) • 2-Way Crossover for true bi-amping of any loudspeaker • Audio Inputs: 2 Single-Ended & 2 Balanced • Audio Outputs: • High-Pass: 2 Single-Ended & 2 Balanced • Low-Pass: 2 Single-Ended 	54.995,00 kr.



SOURCE COMPONENTS

Unit	Description	DKK
MCD600 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Player • Premium 8-Channel, 32-bit Quad Balanced PCM/DSD DAC • Both Stereo Balanced & Unbalanced Fixed & Variable Analog Outputs • Plays SACD, CD, CD-R/RW & DVD-R • Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • Headphone Amp 	73.495,00 kr.
MCD350 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Player • 2-Channel, 32-bit/192kHz balanced PCM/DSD DAC (decodes PCM signals from CDs; DSD signals from SACDs) • Fixed analog stereo balanced and unbalanced outputs • Digital coax and optical outputs • 2x read speed for better reading of damaged CDs and CD-R/RWs 	53.475,00 kr.
MCT500 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Transport • Digital balanced, coax, optical & MCT outputs • Unique MCT output connects to select McIntosh models with a MCT input for playback of SACD high definition audio • Plays SACD, CD, CD-R/RW & DVD-R • Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • 2x read speed 	47.995,00 kr.
MCT80 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Transport sized to match MXA80 Integrated Audio System • Digital coaxial, optical and MCT (DIN) outputs • Unique MCT output connects to select McIntosh models with a MCT input for the purist possible sound quality • Plays SACD, CD, CD-R/RW & user generated DVD or CD Data Discs • Die-cast aluminum tray • Advanced digital servo for faster, quieter & accurate operation • 2x read speed for better reading of damaged CDs & CD-R/RWs 	39.995,00 kr.
MVP901 	<ul style="list-style-type: none"> • Universal Blu-ray DVD/CD Player • Upsamples to 4K Ultra HD • 3D Video • Built in decoding of Dolby True HD & DTS-HD Master Audio + legacy formats • Passes object-based 3D audio formats Dolby Atmos, DTS:X & Auro-3D to compatible processor • Fast Disc Loading • Quad Balanced 32-bit/192kHz DAC for stereo playback of CD/SACD/DVD-Audio discs • BD-Live & File Sharing Over Home Network 	59.995,00 kr.
MR87 	<ul style="list-style-type: none"> • AM/FM/HD Radio Tuner with Multi-Casting • XM-ready • Illuminated Analog Dial and 2-Line Multi-Function Fluorescent Display • Smooth-Acting, Weighted Tuning Mechanism with Animated Dial Pointer • Dual-Differential Remote AM Antenna • External AM and FM Antenna Inputs • 60 Station Presets (20 per band) • Balanced and Single-ended Analog Output • Coaxial and Optical Digital Audio Output 	47.895,00 kr.
MT10 	<ul style="list-style-type: none"> • Belt-Drive Turntable • Dural Aluminum Tone Arm • Weight-Matched Moving Coil Cartridge Included • Precision AC Motor • Magnetic Spindle Bearing • Strobe Speed Control • Illuminated Speed Meter • Multi-Layered Damped Chassis 	109.495,00 kr.
MT5 	<ul style="list-style-type: none"> • Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Magnetic Spindle Bearing • Multi-Layered Damped Chassis • Includes Plexi Dustcover 	69.995,00 kr.
MT2 	<ul style="list-style-type: none"> • Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • Plays 33-1/3 and 45 rpm records • High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Resonance optimized and highly compressed wood base with black lacquer finish • Includes Plexi Dustcover 	44.795,00 kr.
MT1100 	<ul style="list-style-type: none"> • Belt-Drive Integrated Turntable • Includes: power amplifier, vacuum tube preamplifier, shielded phono preamplifier, 1 unbalanced auxiliary input, digital coaxial & optical inputs, Bluetooth receiver, subwoofer output, stereo speaker outputs, headphone jack • Plays 33-1/3 & 45 rpm records • Machined aluminum platter & tonearm • Anti-skate • Industrial grade permanent magnet AC synchronous motor with 2-speed pulley • Manual speed change • Includes Sumiko Olympia Moving Magnet cartridge • Class D amplifier: 80 Watts into 4 Ohms or 50 Watts into 8 Ohms 	64.995,00 kr.





INTEGRATED AUDIO SYSTEMS

Unit	Description	DKK
RS200 	<ul style="list-style-type: none"> • Next generation home audio wireless speaker • 650 Watts of total power • Two 4" x 6" woofers, four 2" midranges, two 3/4" tweeters • Apple® AirPlay® 2 • Bluetooth® 5.0 • DTS Play-Fi® (with built-in interfaces for streaming services including Amazon Prime Music, Pandora®, Qobuz, SiriusXM®, Spotify® & TIDAL) • DLNA • Works With Alexa • Qualcomm® aptX™ HD & Low Latency • USB, HDMI, Optical, & AUX inputs • Sub output • 3-position EQ switch • Connect TV for better sound 	29.895,00 kr.
RS100 	<p>*NOT AVAILABLE IN ALL TERRITORIES* Wireless speaker featuring DTS Play-Fi technology • Start with 1 then add more to build system • Up to 16 can be added to a Wi-Fi network • Connect to existing Wi-Fi & then stream music library from mobile device via free Apple & Android app • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • AUX input for non-streaming use • Subwoofer output</p>	9.875,00 kr.
McAire 	<ul style="list-style-type: none"> • Built in AirPlay® allows wireless streaming of music via Wi-Fi network from Mac or PC based iTunes® library, iPad®, iPhone® or iPod touch® • USB docking is available for all day playback and charging • Computers and TVs may be quickly connected for full range, high fidelity sound • Two 4" woofers, two 2" midranges, two 3/4" tweeters • Delivers the legendary McIntosh look and sound quality in a compact size 	28.975,00 kr.
MXA80 	<ul style="list-style-type: none"> • Compact System • 2 x 50 Watts • Pair of specially designed 8 Ohm 2-way speakers • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD) images high quality recordings like conventional speakers • Power Guard to Prevent Clipping and Speaker Damage • 5 Step Bass Boost Control • Polished Stainless Steel Chassis 	58.495,00 kr.








MEDIA STREAMERS

Unit	Description	DKK
MB50 	<p>*NOT AVAILABLE IN ALL TERRITORIES* Streaming audio player featuring DTS Play-Fi technology • Connects to existing Wi-Fi to turn traditional audio system into a wireless audio system • Free Apple & Android app to stream music library stored on mobile device • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Analog & digital inputs for mini-preamp functionality • Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • Narrow chassis</p>	18.475,00 kr.
MS500 	<ul style="list-style-type: none"> • Seamlessly integrates internet based streaming music & locally stored digital music into one comprehensive device • Up to 24 bit/192kHz output • Built-in interfaces to streaming services such as Deezer, Murfie, Pandora®, Rhapsody®, SiriusXM®, Slacker, Spotify® & TIDAL (list subject to change) • Ultra-quiet thanks to solid state drive & fanless processor with no noisy cooling fans • Synchronizes content stored on networked computers so it is readily playable • Secure back to Amazon Cloud Drive, Apple iCloud or Google Drive • Linux based OS • 3 USB ports to connect external drives • 1 additional independent audio zone can be created when using an external DAC 	59.995,00 kr.



LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	DKK
XRT2.1KL 	<ul style="list-style-type: none"> Reference Series Dual-Column 4-Way Ported Line-Source • 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3/4" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Left speaker only (see XRT2.1KR for matching right speaker) 	Pr. styk 645.995,00 kr. Pr. sæt 1.291.990,00 kr.
XRT2.1KR 	<ul style="list-style-type: none"> Reference Series Dual-Column 4-Way Ported Line-Source • 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3/4" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Right speaker only (see XRT2.1KL for matching left speaker) 	Pr. styk 645.995,00 kr. Pr. sæt 1.291.990,00 kr.
XRT1.1KL 	NEW • Dual-Column 4-Way Ported Line Array • 70 Total Drivers • 4 x 6.5" Woofers • 2 x 6.5" Low Frequency Midranges • 24 x 2" Upper Frequency Midranges • 40 x 3/4" Tweeters • 16 Hz - 45 kHz Response • 89dB SPL • 1,200 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 5.9' (1.8 meters) tall • Piano Black finish • Left speaker only (see XRT1.1KR for matching right speaker)	Pr. styk 295.995,00 kr. Pr. sæt 591.990,00 kr.
XRT1.1KR 	NEW • Dual-Column 4-Way Ported Line Array • 70 Total Drivers • 4 x 6.5" Woofers • 2 x 6.5" Low Frequency Midranges • 24 x 2" Upper Frequency Midranges • 40 x 3/4" Tweeters • 16 Hz - 45 kHz Response • 89dB SPL • 1,200 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 5.9' (1.8 meters) tall • Piano Black finish • Right speaker only (see XRT1.1KL for matching left speaker)	Pr. styk 295.995,00 kr. Pr. sæt 591.990,00 kr.








LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	DKK
CK200	In Wall Mounting Kit for XCS200	6.595,00 kr.
	<ul style="list-style-type: none"> • In-Ceiling Loudspeaker • Perfect for custom installed distributed audio or as home theater surround sound speakers • 15 - 250 Watt Power Rating • 48Hz - 22kHz Response • 1 x 8" woven glass fiber woofer • 2 x 2" inverted Titanium dome midranges • 1 x 3/4" Titanium dome tweeter • Midranges and tweeter are housed in a rotating array • Paintable magnetic grille with minimum visible mounting flange • Voice matched to WS500 & WS300 speakers 	13.995,00 kr.
RK200	Construction Rough-In Kit for CS200	595,00 kr.
	<ul style="list-style-type: none"> • True 3-Way Compact Bookshelf Speaker • 40 Hz - 45 kHz Frequency Response • 1 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 1 x 3/4" Titanium Super Tweeter • 300-Watt Music Power-Handling • Patented McIntosh Binding Posts • Front-Panel McIntosh Logo Illumination using Power Control • Premium cabinet finishes include Red Walnut, Gloss Black 	Pr. styk 19.995,00 kr. Pr. sæt 39.990,00 kr.
	<ul style="list-style-type: none"> • True 4-way Floor-Standing Tower Speaker • 30 Hz - 45 kHz Frequency Response • 4 x 6" LDHP Woofers • 8 x 2" Titanium Midrange • 2 x 2" Titanium Tweeters • 1 x 3/4" Titanium Super Tweeter • Dual Sets of Patented McIntosh Binding Posts Enable Bi-Wire or Bi-Amplification • 600-Watt Music Power Handling • Front-Panel McIntosh Logo Illumination Using Power Control • Premium Cabinet Finishes Include Red Walnut, Gloss Black 	Pr. styk 47.995,00 kr. Pr. sæt 95.990,00 kr.
	<ul style="list-style-type: none"> • True 3-Way Center-Channel Speaker • 80Hz to 45 kHz Frequency Response • 2 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 1 x 3/4" Titanium Super Tweeter • 300-Watt Music Power-Handling • Voiced to Match XR50 & XR100 • Patented McIntosh Binding Posts • Premium Cabinet Finishes include Red Walnut, Gloss Black (Pear Maple Discontinued) 	Pr. styk 23.995,00 kr.
	<ul style="list-style-type: none"> • IN-Wall THX Licensed Dipole Surround Speaker • 200 Watts Max Continuous Power • 2 x 5" Polypropylene Woofers • 2 x 1" Aluminum Dome Tweeters • Paintable Frame & Metal Grill <p align="center">SOLD IN PAIRS</p>	27.995,00 kr.
	<ul style="list-style-type: none"> • ON-Wall THX Licensed Dipole Surround Speaker • 200 Watts Max Continuous Power • 2 x 5" Polypropylene Woofers • 2 x 1" Aluminum Dome Tweeters • Paintable Frame & Metal Grill <p align="center">SOLD IN PAIRS</p>	27.995,00 kr.
RK100	Construction Rough-In Kit for CS100	450,00 kr.
	<ul style="list-style-type: none"> • In-Wall 3-Way Loudspeaker • Perfect for custom installed distributed audio or home theater • 15 - 250 Watt Power Rating • 80Hz - 20kHz Response • 1 x 8" woven glass fiber woofer • 2 x 2" inverted Titanium dome midranges • 1 x 3/4" Titanium dome tweeter • Fully enclosed to deliver incredible performance in any environment • Fits in standard 2x4 wall construction • Paintable magnetic grille with minimum visible mounting flange • Voice matched to WS500 & CS200 speakers 	Pr. styk 24.995,00 kr.
RK300	Construction Rough-In Kit for WS300	595,00 kr.

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)

Unit	Description	DKK
RK300	Construction Rough-In Kit for WS300	595,00 kr.
WS350 	<ul style="list-style-type: none"> • In-Wall 3-Way Speaker • 200 Watts Max Continuous Power Handling • 5-Tweeter Bessel Array • One 8" Woofer • One 4" Midrange • Five 1" Dome Tweeters • Deep-Drawn Sealed Aluminum Enclosure • Paintable Frame & Metal Grille 	Pr. styk 20.475,00 kr.
RK320	Construction Rough-In Kit for WS350	450,00 kr.
WS500 	<ul style="list-style-type: none"> • In-Wall 3-Way Loudspeaker • Perfect for custom installed distributed audio or home theater • 15 - 250 Watt Power Rating • 80Hz - 20kHz Response • 2 x 6-1/2" woven glass fiber woofers • 2 x 2" inverted Titanium dome midranges • 1 x 3/4" Titanium dome tweeter • Fully enclosed to deliver incredible performance in any environment • Fits in standard 2x4 wall construction • Paintable magnetic grille with minimum visible mounting flange • Voice matched to WS300 & CS200 speakers 	Pr. styk 28.995,00 kr.
RK500	Construction Rough-In Kit for WS500	595,00 kr.

ACCESSORIES

Unit	Description	DKK
MPC1500 	<ul style="list-style-type: none"> • AC Isolation Transformer & AC Switching Hub • 12 Rear Panel AC Outlets with Programmable Power Control Options • Front and Rear Panel LED Status Indicators • Front Panel Back-Lit Meters Display Line Voltage & Amperage 	53.995,00 kr.
MPC500 	<ul style="list-style-type: none"> • AC power line surge protection via 3 thermally protected metal-oxide varistors (TMOVs) • Secondary surge protection of ethernet, coaxial, & other low voltage devices via Gas Discharge Tubes (GDT), Positive Temperature Coefficient (PTC) thermistors and Transient Voltage Suppression (TVS) components • Connect 4-8 components depending on receptacle type • Electromagnetic interference (EMI) filtering • Over/under voltage protection • Display lists input voltage, current draw, or total power 	23.895,00 kr.
MC CLOCK 	The McIntosh Clock boast our trademak glass front pannel and two of our blue meters , One to show the hour and the other to show minutes .	17.995,00 kr.
LB100 	Unmistakably McIntosh. The LB100 Light Box proudly displays the "Handcrafted In The USA Since 1949" statement as a badge of honor. A must for every McIntosh owner. Approximately the size of a McIntosh CD player. Includes Power Control for seamless on/off with other McIntosh components.	13.300,00 kr.
BLI-23 (pair)	Balanced Line Integrator, 2 XLR Inputs & 3 XLR Outputs	2.795,00 kr.
MCBOOK 	"For the Love of Music" – The History of McIntosh	1.350,00 kr.
DA2 Upgrade Kit 	NEW • Dealer installed upgrade to DA1 Digital Audio Module • Models that can be upgraded to DA2: MA9000, MA8900, MA7200, MA5300, MAC7200, C49 • 7 inputs: 2 Optical, 2 Coax, 1 USB, 1 MCT, 1 HDMI (ARC) • DSD512 & DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC • Due to the technical nature of the DA2 upgrade, the upgrade must be performed by a qualified trained professional at an Authorized McIntosh Dealer or Authorized McIntosh Service Agency	9.900,00 kr.
TM3 Tuner Module 	<ul style="list-style-type: none"> • AM/FM/HD Radio Tuner Module for use with MA6600 Integrated Amplifier • Includes Dual-Differential Remote AM Antenna • External AM and FM antenna inputs 	7.700,00 kr.

AUDIO CABLES

Unit	Description	DKK
CBA1M	BALANCED AUDIO SINGLE 1-METER	3.795,00 kr.
CBA2M	BALANCED AUDIO SINGLE 2-METER	4.800,00 kr.
CA1M	UNBALANCED AUDIO PAIR 1-METER	5.795,00 kr.
CA2M	UNBALANCED AUDIO PAIR 2-METER	6.595,00 kr.
CDA1M	COAX DIGITAL SINGLE 1-METER	4.450,00 kr.
CDA2M	COAX DIGITAL SINGLE 2-METER	5.300,00 kr.
CC1M	CONTROL SINGLE 1-METER	645,00 kr.
CC2M	CONTROL SINGLE 2-METER	745,00 kr.
CS2M	SPEAKER SINGLE 2-METER	10.995,00 kr.
CS3M	SPEAKER SINGLE 3-METER	13.995,00 kr.

PS AUDIO SCANDINAVIA

DER TAGES FORBEHOLD FOR TRYK- OG TASTEFEJL, PRISÆNDRINGER OG UDSOLGTE VARER.