










Prisliste 2020



McIntosh®


LEGENDARY PERFORMANCE™








PS Audio
Scandinavia


POWER AMPS







Unit	Description	DKK
MC2KW 	<ul style="list-style-type: none"> • 1 x 2000 Watts • Reference Series • Quad-Balanced Design • Separate Positive & Negative Amplifiers • 3 Full Sets of Terminals for Tri-Wiring @ 8, 4 & 2 Ohms • Silent Convection Cooling • Safe Operation to Below 2 Ohms 	399.000,00 kr.
MC901 	NEW • 1 x 300 Watts vacuum tube and 1 x 600 Watts solid state • The ultimate solution for bi-amping loudspeakers: 300 Watt vacuum tube amplifier & 600 Watt solid state amplifier on one chassis • Vacuum tube section powers mid & upper drivers • Solid state section drives woofers • Full power into 2, 4 or 8 Ohms via Unity Coupled Circuit output transformer for tubes & Autoformer™ for solid state • Adjustable crossover filters • Power Guard ® for solid state • New Power Guard Screen Grid Sensor™ (SGS) for tubes • Sentry Monitor™ • Quad-Balanced Design • New DualView™ Power Output Meter • McIntosh Monogrammed Heatsinks™ • Power Control • Solid Cinch™ speaker binding posts	174.995,00 kr.
MC1.25KW 	<ul style="list-style-type: none"> • 1 x 1200 Watts • Redesigned from top to bottom • Autoformer for 2, 4 & 8 Ohms • Exclusive McIntosh Power Assurance System • Direct LED Backlighting • 50% increase in filter capacity from previous model • McIntosh Monogrammed Heatsinks™ • Updated power transformer, internal wiring, circuit components and industrial design • Power management system • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	124.995,00 kr.
MC611 	<ul style="list-style-type: none"> • 1 x 600 Watts • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Direct LED Backlighting • 2x filter capacity from previous model results in 55% increase in dynamic headroom from 1.8dB to 2.8dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	74.995,00 kr.
MC830 	<ul style="list-style-type: none"> • 1 x 300 Watts into 8 Ohm or 480 Watts into 4 Ohm • Open chassis industrial design similar to our popular MC275 Vacuum Tube Amplifier and MA252 & MA352 Integrated Amplifiers • Pair with the matching C8 Vacuum Tube Preamplifier • Direct coupled output • Fast-responding Dual Scale Watt meter • McIntosh Monogrammed Heatsinks™ • Power Guard® • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts • Die cast aluminum name badges • Remote Power Control with Meter Light Control • Large Gold Plated Five-Way Binding Posts • 1/2" Thick Glass Front Panel with Tube View 	40.000,00 kr.
MC2301 	<ul style="list-style-type: none"> • 1 x 300 Watts • Balanced Unity-Coupled Vacuum Tube Design • Peak Responding Wattmeter • Two Balanced Inputs/Outputs • Remote Power Control with Meter Light Control • Large Gold Plated Five-Way Binding Posts • 1/2" Thick Glass Front Panel with Tube View 	124.995,00 kr.
MC462 	<ul style="list-style-type: none"> • 2 x 450 Watts • Output Autoformers for 2, 4 & 8 Ohms • Nearly 2x filter capacity from previous model results in 66% increase in dynamic headroom from 1.8dB to 3.0dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Direct LED Backlighting • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Quad-Balanced Design • Power Control • Solid Cinch™ speaker binding posts 	89.995,00 kr.
MC312 	<ul style="list-style-type: none"> • 2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 2x filter capacity from previous model results in 27% increase in dynamic headroom from 1.8dB to 2.3dB • McIntosh Monogrammed Heatsinks™ • ThermalTrak™ Output Transistors • Direct LED Backlighting • Updated internal wiring, circuit components and industrial design • Power Guard® • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts 	69.995,00 kr.
MC152 	<ul style="list-style-type: none"> • 2 x 150 Watts • Slim Chassis Design • Output Autoformer for 2, 4 & 8 Ohms • Peak-Responding Wattmeter • Power Guard to Prevent Clipping • ThermalTrak™ Output Transistors • Patented McIntosh Speaker Binding Posts 	49.995,00 kr.





MC1502 	<ul style="list-style-type: none"> • 2 x 150 Watts • Identical audio specifications and sound reproduction performance of the heralded MC2152 but in a more customary McIntosh design • Shares the timeless styling of our classic MC275 • Quieter than the already quiet MC275 • Unity Coupled Circuit Output Transformers for 2, 4 & 8 Ohms • (8) KT88, (4) 12AX7A and (4) 12AT7 vacuum tubes • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts 	110.000,00 kr.
MC275 	<ul style="list-style-type: none"> •Version VI Model• Same feature set as MC275LE but with polished stainless chassis •2 X 75 Watts •Outputs for 4, 8, 16 Ohms •Sentry Monitor Protection •Unique Tube Illumination to Indicate Operational Status •Front Apron Power Switch •Stereo/Mono Switch •Patented McIntosh Speaker Binding Posts •Power Control to Enable Remote On/Off with McIntosh Preamplifiers 	59.995,00 kr.







POWER AMPS		
Unit	Description	DKK
MC2152 	<ul style="list-style-type: none"> • 70th Anniversary Model with anniversary markings • 2 x 150 Watts • Unity Coupled Output Transformers for 2, 4 & 8 Ohms • (8) KT88, (4) 12AX7A and (4) 12AT7 vacuum tubes • Bead blasted black anodized aluminum chassis accentuated with matte finish carbon fiber side panels • Sentry Monitor™ • Power Control • Solid Cinch™ speaker binding posts 	149.995,00 kr.
MC303 	<ul style="list-style-type: none"> • 3 x 300 Watts • Output Autoformers • Peak Responding Wattmeters • LED Fiber-Optic Illumination • Exclusive McIntosh Power Assurance System • 60 Amps Output Current • Large Gold Plated Five-Way Binding Posts 	114.795,00 kr.
MC255 	<ul style="list-style-type: none"> • 250 Watts x 3 Channels; 200 Watts x 5 Channels • Designed for home theaters • TripleView™ Power Output Meter indicates the real time power reading of the 3 front channels • More than 100% increase in dynamic headroom • McIntosh Monogrammed Heatsinks™ and a specially wound toroidal isolation power transformer for low noise • Power Guard® • Sentry Monitor™ • Power Control • Standard gold-plated binding posts • 2 channels can power a separate zone • Direct LED Backlighting 	79.995,00 kr.
MC257 	<ul style="list-style-type: none"> • 250 Watts x 3 Channels; 200 Watts x 7 Channels • Designed for home theaters • TripleView™ Power Output Meter indicates the real time power reading of the 3 front channels • 94% increase in dynamic headroom • McIntosh Monogrammed Heatsinks™ and a specially wound toroidal isolation power transformer for low noise • Power Guard® • Sentry Monitor™ • Power Control • Standard gold-plated binding posts • 2 channels can power a separate zone • Direct LED Backlighting 	98.995,00 kr.
MC8207 	<ul style="list-style-type: none"> • 7 x 200 Watts • Two-Zone Operation • DPM Circuit Design Ensures Full Power at 4 or 8 Ohms • Theater-Friendly LED Meters • LED Fiber-Optic Panel Illumination • Exclusive McIntosh Power Assurance System • Remote Power Control Trigger • Multi-Way Speaker Binding Posts 	64.995,00 kr.
MI128 	<ul style="list-style-type: none"> • 8 x 120 Watts into 8 Ohms or 150 Watts into 4 Ohms • 8-channel Class D amplifier for custom install distributed audio, home theater or stereo listening • Installer-friendly physical dimensions • 2U rack mountable • Unbalanced inputs • 2-pole Phoenix style push-in speaker terminals • Volume controls for volume balancing • 2 digital audio inputs • Channel summing circuits for easy mono signal distribution • Loudspeaker Guard • Sentry Monitor™ • BUS input & outputs to easily distribute a stereo signal to multiple outputs and/or multiple amplifiers • Eco-friendly on/off signal sensing 	34.995,00 kr.
MI254 	<ul style="list-style-type: none"> • 4 x 250 Watts into 8 Ohms or 300 Watts into 4 Ohms • 4-channel Class D amplifier for custom install distributed audio, home theater or stereo listening • Installer-friendly physical dimensions • 2U rack mountable • McIntosh Watt Meters that display the summed power output of channels 1 + 2 and channels 3 + 4 • Balanced & unbalanced inputs • 5-way speaker binding posts • Loudspeaker Guard • Sentry Monitor™ • BUS input & outputs to easily distribute a stereo signal to multiple outputs and/or multiple amplifiers • Eco-friendly on/off signal sensing 	43.795,00 kr.
MI347 	<p>Channels: 125 Watts into 8 Ohms or 200 Watts into 4 Ohms • 7-channel Class D amplifier for home theater, custom install, or stereo listening • Rack-friendly physical dimensions • 3U rack mountable • Uses highly sophisticated closed loop digital switching amplifiers paired with extremely robust power supplies that produce audio performance levels rarely heard in home theaters • Balanced & unbalanced inputs • 5-way speaker binding posts • Power Guard® • Sentry Monitor™ • Eco-friendly on/off signal sensing • Front panel multi-color LED indicators display the status of each channel • Pair with rack mountable MX100 A/V Processor • If more than 7 home theater channels, use with rack mountable MI254 4-Channel or MI128 8-Channel Amplifier</p>	50.000,00 kr.

INTEGRATED AMPLIFIERS		
Unit	Description	DKK
MA12000 	<ul style="list-style-type: none"> • 2 x 350 Watts • Hybrid: Vacuum Tube preamp + solid state power amp • (4) 12AX7A vacuum tubes in preamp • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 2 High-Level Balanced Inputs • MC & MM Phono Inputs (both adjustable loading) • DA2 Digital Audio Module with 7 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT, 1 HDMI (ARC only) • DSD512 and DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC used in Quad Balanced mode • Double filter capacity compared to our other integrations for even better low frequency performance • McIntosh Monogrammed Heatsinks™ • Discrete 8-Band Equalizer • Premium gold-plated solid brass analog connectors • 1/4" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Solid Cinch™ speaker binding posts • Upgraded audio components 	140.000,00 kr.
MA9000 	<ul style="list-style-type: none"> • 2 x 300 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 2 High-Level Balanced Inputs • MC & MM Phono Inputs (both adjustable loading) • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 8-Band Equalizer • Premium gold-plated solid brass analog connectors • 1/4" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Solid Cinch™ speaker binding posts • Upgraded audio components 	108.995,00 kr.
MA8900 	<ul style="list-style-type: none"> • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 6 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • New McIntosh Monogrammed Heatsinks™ • Discrete 5-Band Equalizer • 1/4" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	79.995,00 kr.
MA5300 	<ul style="list-style-type: none"> • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • 4 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • DA1 Digital Audio Module w/ 6 inputs • DSD256 & DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • McIntosh Monogrammed Heatsinks™ • 1/4" High Drive Headphone Jack w/ Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Bass & Treble tone controls 	53.795,00 kr.
MA352 	<ul style="list-style-type: none"> • 2 x 200 Watts into 8 Ohm or 320 Watts into 4 Ohm • Hybrid: Vacuum Tube preamp + solid state power amp • (2) 12AX7A & (2) 12AT7 vacuum tubes in preamp • Direct coupled amp • 3 Unbalanced & 2 Balanced Inputs • Moving Magnet Input • 5-Band tone control • McIntosh Monogrammed Heatsinks™ • 1/4" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Retro styling • Die cast aluminum name badges • Remote control 	64.995,00 kr.
MA252 	<ul style="list-style-type: none"> • 2 x 100 Watts into 8 Ohm or 160 Watts into 4 Ohm • Hybrid: Vacuum Tube preamp + solid state power amp • (2) 12AX7a & (2) 12AT7 vacuum tubes in preamp • Direct couple amp • 2 Unbalanced & 1 Balanced Inputs • Moving Magnet Input • Bass & Treble tone controls • McIntosh Monogrammed Heatsinks™ • 1/4" High Drive Headphone Jack • Power Guard® • Sentry Monitor™ • Power Control • Retro styling • Die cast aluminum name badge on each side • Remote control 	39.795,00 kr.
MA7200 	<ul style="list-style-type: none"> • 2 x 200 Watts • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • 1/4" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	59.850,00 kr.
RECEIVERS		







Unit	Description	DKK
MAC7200 	<ul style="list-style-type: none"> • 2 x 200 Watts • Built in AM/FM Tuner • Output Autoformers for 2, 4 & 8 Ohms • 5 High-Level Unbalanced & 1 High-Level Balanced Inputs • MC & MM Phono Inputs • New DA1 Digital Audio Module with 6 inputs • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • DSD256 and DXD 384kHz support • McIntosh Monogrammed Heatsinks™ • Bass & Treble Tone Controls • ¼" High Drive Headphone Jack with Headphone Crossfeed Director (HXD®) • Power Guard® • Sentry Monitor™ • Home Theater PassThru • Power Control • Upgraded audio components 	73.995,00 kr.





HEADPHONE AMPLIFIERS		
Unit	Description	DKK
MHA150 	<ul style="list-style-type: none"> • Headphone Amplifier • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD®) images quality recordings like conventional speakers • Power Guard • 50 Watt stereo speaker terminals • Compact size for placement flexibility • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • 1 USB Input at 32-bit/384kHz • 1 MCT Input for SACD playback from MCT450 Transport 	48.550,00 kr.
MHA50 	<ul style="list-style-type: none"> • Portable Decoding Amplifier • Comparably sized to smartphones • Inputs: wired inputs for iOS devices & Android devices with USB On-The-Go technology; Mac® & Windows® PCs; Bluetooth® 4.1 with aptX™ • 3.5mm gold plated headphone jack • High-performance DAC supports 32-bit/192kHz hi-res audio, up to DSD128 & DXD384 files & asynchronous USB audio • Up to 6 hours of playback on a single battery charge • 2 gain settings drive 8-600 Ohms • Headphone Crossfeed Director (HXD®) • Includes: leather case; 4 USB adapter cables; wall mount charger 	6.895,00 kr.
AUDIO PREAMP CONTROL CENTERS		
Unit	Description	DKK
C1100C 	<ul style="list-style-type: none"> • Controller for Reference series multi-chassis C1100T Vacuum Tube Preamp • Keeps control & power sections separate from the audio section • Left & right channels are electrically & mechanically isolated from each other to allow true dual mono operation • Connected to C1100T by specially designed, shielded & high performance umbilical cables • Requires use of C1100T 	68.785,00 kr.
C1100T 	<ul style="list-style-type: none"> • Vacuum Tube Preamp to be used with C1100C Controller • High level inputs have the lowest noise of any McIntosh preamplifier ever produced • 6 Balanced (XLR) Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 12 vacuum tubes • 2 Balanced (XLR) Outputs • 2 Unbalanced Outputs • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD) • Requires use of C1100C 	68.995,00 kr.
D1100 	<ul style="list-style-type: none"> • Reference Level Digital Preamplifier with our most advanced DAC • 8-channel, 32-bit DAC is used in Quad Balanced mode • Supports DSD64, DSD128, DSD256, DXD 352.8kHz & DXD 384kHz • 9 Inputs: 3 coax, 3 optical, 1 each MCT (for SACD playback from MCT450 Transport), AES/EBU & USB • 3 sets of Balanced and Unbalanced stereo outputs (1 set fixed volume, 2 sets variable) • 1 Headphone Jack (¼") with Headphone Crossfeed Director (HXD®) • Audio channels & power supplies are electrically isolated from each other for dual mono operation • Can be used by itself or in tandem with analog C1100 Vacuum Tube Preamp • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis • RS232 	74.995,00 kr.
C22 	<p>C22 2-CHANNEL VACUUM TUBE PREAMPLIFIER Mk V</p> <ul style="list-style-type: none"> • C22 Mk V is the latest McIntosh vacuum tube preamplifier to carry the cherished C22 model number and its signature glass and aluminum front panel design • (5) 12AX7A and (1) 12AT7 vacuum tubes • All analog design and a retro look • Inputs: 2 balanced, 3 unbalanced, 1 Moving Coil, 1 Moving Magnet (phono inputs are adjustable) • Outputs: 2 balanced, 2 unbalanced • Bypassable bass and treble controls • High Drive headphone amplifier with Headphone Crossfeed Director (HXD®) • Power Control 	60.000,00 kr.




C70 	<ul style="list-style-type: none"> • 70th Anniversary Model with anniversary markings • Vacuum Tube Stereo Preamplifier • (5) 12AX7A and (1) 12AT7 vacuum tubes • All analog design and a retro look • 2 balanced, 3 unbalanced, 1 Moving Coil, 1 Moving Magnet input (phono inputs are adjustable) • 2 balanced, 2 unbalanced outputs • Bass and treble tone controls • High Drive headphone amplifier with Headphone Crossfeed Director (HXD®) technology • Power Control 	68.785,00 kr.
C8 	<ul style="list-style-type: none"> • (4) 12AX7A vacuum tubes • Inputs: 2 Unbalanced, 1 Balanced, 1 Moving Coil, 1 Moving Magnet • Outputs: 2 Unbalanced (1 configurable as Subwoofer out), 1 Balanced • Open chassis industrial design similar to our popular MC275 Vacuum Tube Amplifier and MA252 & MA352 Integrated Amplifiers • Pair with the matching MC830 Solid State Amplifier • Bass & Treble tone controls • 1/4" High Drive Headphone Jack • Power Control • Die cast aluminum name badges • Remote control • Optional dealer installed upgrade to DA2 Digital Audio Module available 	35.000,00 kr.
C2700 	<ul style="list-style-type: none"> • Vacuum Tube Preamplifier • 3 Balanced Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced Outputs • 4 Unbalanced Outputs • DA2 Digital Audio Module with 7 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT, 1 HDMI (ARC only) • DSD512 and DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC used in Quad Balanced mode • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD®) • Output Meters 	79.995,00 kr.
C53 	<ul style="list-style-type: none"> • 3 Balanced Inputs • 4 Unbalanced Inputs • MC & MM Phono Inputs • 3 Balanced Outputs • 4 Unbalanced Outputs • DA2 Digital Audio Module with 7 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT, 1 HDMI (ARC only) • DSD512 and DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC used in Quad Balanced mode • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD®) • 8 Band Equalizer • Output Meters 	79.995,00 kr.
C49 	<ul style="list-style-type: none"> • 2 Balanced Inputs • 3 Unbalanced Inputs • MC & MM Phono Inputs • 2 Balanced Outputs • 3 Unbalanced Outputs • DA1 Digital Audio Module with 6 inputs: 2 Optical & 2 Coax (24-bit/192kHz), 1 USB (32-bit/384kHz), 1 MCT • DSD256 and DXD 384kHz support • 8-channel, 32-bit/192kHz DAC used in Quad Balanced mode • Front Panel Headphone Jack with Headphone Crossfeed Director (HXD®) 	48.550,00 kr.










PHONO PREAMPLIFIERS		
Unit	Description	DKK
MP1100 	<ul style="list-style-type: none"> Dedicated Vacuum Tube Phono Preamplifier • Fully Balanced Vacuum Tube Phono Stage • Four 12AX7A Vacuum Tubes (2 tubes per channel) • 3 sets of RCA Phono Inputs (XLR connectors available on 1 of the inputs) • 4 Pre-Programmed & 5 Programmable Profiles • 8 Capacitance & 7 Resistance Settings • 5 Analog Equalization Curves • 2 Analog Noise Filters • Adjustable Gain • 1 pair of Balanced & Unbalanced Line Inputs & Fixed Outputs • Coax, Optical & USB Digital Outputs • Rip to computer via USB • Digital Output Clipping Indicator • Mono setting • Dual Mono design • Polished Stainless Steel & hairline brushed black Titanium Stainless Steel chassis 	83.995,00 kr.
MP100 	<ul style="list-style-type: none"> Dedicated Phono Preamplifier • Adjustable Moving Coil & Moving Magnet inputs (6 settings each) • Balanced & Unbalanced Analog Outputs • Coax, Optical and USB Digital Outputs • Rip to computer via USB • Digital output clipping indicator • Mono switch • Narrow chassis 	18.995,00 kr.
AUDIO VIDEO CONTROL CENTER/ROOM CORRECTION SYSTEM		
Unit	Description	DKK
MX170 	<ul style="list-style-type: none"> 16 Channel A/V Processor used in 15.1 (all 16 are balanced) • Supports Dolby Atmos, DTS:X & Auro-3D • 8 HDMI inputs & 4 HDMI outputs • All HDMI ports are HDCP 2.2 w/18Gbps of bandwidth • Supports 4K Ultra HD native sources and full 4:4:4 color spacing • Supports Dolby Vision™, HDR10 and HLG • eARC on 1 HDMI output • 3D video supported • RoomPerfect room correction • HDBaseT output • 2 sets of stereo balanced, 4 sets of stereo unbalanced, dedicated phono & 7.1 multi-channel unbalanced inputs • 4 optical, 3 coaxial and 1 USB that each accept up to 24-bit/192kHz • Easy to use and robust setup program allows for great customization and optimization 	153.785,00 kr.
MX123 	<ul style="list-style-type: none"> 15 Channel A/V Processor used in 13.2 • Supports Dolby Atmos, DTS:X & Auro-3D • Supports 4K Ultra HD native sources plus upscaling • 3D video supported • HDMI: 7 inputs & 3 outputs (all HDCP 2.3, 4K Ultra HD at 50/60Hz, 4:4:4 color, Rec. 2020) • Supports Dolby Vision™, HDR10, HLG & IMAX Enhanced • eARC on 1 HDMI output • Inputs: 1 stereo balanced; 7 stereo unbalanced + 1 dedicated phono; 7.1 multi-channel unbalanced; 3 component; 4 composite; 2 optical & 2 coax digital audio • DSD128 and ALAC 192kHz • Audyssey MultEQ XT32 room correction • Airplay 2, Bluetooth, Spotify Connect, TuneIn • Zonable • 9 band equalizer + bass and treble • Dual band WiFi 	78.995,00 kr.
MX100 	<p>Streamlined McIntosh Home Theater Performance • 13 Channel A/V Processor used in 11.2 (aka 7.2.4) • Installer and rack-friendly physical dimensions • 2U rack mountable • Dolby: Dolby Atmos, Dolby Surround Upmixer • DTS: DTS-X, Neural:X Surround Upmixer • Supports 4K Ultra HD native sources • HDMI: 4 inputs & 1 output • Each HDMI port: HDCP 2.2; 18Gbps of bandwidth to support High Dynamic Range (HDR) formats Dolby Vision™, HDR10 and HLG; 4K Ultra HD at 50/60Hz; 4:4:4 color spacing; Rec. 2020; and 3D video pass-through • Enhanced Audio Return Channel (eARC) included on HDMI output • 2 optical & 2 coax digital audio inputs • Balanced (XLR) outputs only • Audyssey MultEQ XT32 room correction • Bass and Treble tone controls • RS232 control protocol • <u>Pair with rack mountable home theater amplifiers MI347, MI254 or MI128</u></p>	50.000,00 kr.
MEN220 	<ul style="list-style-type: none"> RoomPerfect Room Correction Custom EQ Application (that runs on any Windows PC) 2-Way Crossover for true bi-amping of any loudspeaker Audio Inputs: 2 Single-Ended & 2 Balanced Audio Outputs: <ul style="list-style-type: none"> High-Pass: 2 Single-Ended & 2 Balanced Low-Pass: 2 Single-Ended 	54.995,00 kr.

SOURCE COMPONENTS		
Unit	Description	DKK
MCD600 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Player • Premium 8-Channel, 32-bit Quad Balanced PCM/DSD DAC • Both Stereo Balanced & Unbalanced Fixed & Variable Analog Outputs • Plays SACD, CD, CD-R/RW & DVD-R • Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • Headphone Amp 	73.495,00 kr.
MCD350 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Player • 2-Channel, 32-bit/192kHz balanced PCM/DSD DAC (decodes PCM signals from CDs; DSD signals from SACDs) • Fixed analog stereo balanced and unbalanced outputs • Digital coax and optical outputs • 2x read speed for better reading of damaged CDs and CD-R/RWs 	53.475,00 kr.
MCT500 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Transport • Digital balanced, coax, optical & MCT outputs • Unique MCT output connects to select McIntosh models with a MCT input for playback of SACD high definition audio • Plays SACD, CD, CD-R/RW & DVD-R • Front panel USB input • Premium aluminum die cast CD tray • Popular file formats such as AAC, AIFF, ALAC, DSD (up to DSD128), FLAC, MP3, WAV (up to 24-bit/192kHz) & WMA can be played from user generated CD or DVD Data Discs & USB flash drives • 2x read speed 	47.995,00 kr.
MCT80 	<ul style="list-style-type: none"> • 2-Channel SACD/CD Transport sized to match MXA80 Integrated Audio System • Digital coaxial, optical and MCT (DIN) outputs • Unique MCT output connects to select McIntosh models with a MCT input for the purist possible sound quality • Plays SACD, CD, CD-R/RW & user generated DVD or CD Data Discs • Die-cast aluminum tray • Advanced digital servo for faster, quieter & accurate operation • 2x read speed for better reading of damaged CDs & CD-R/RWs 	39.995,00 kr.
MVP901 	<ul style="list-style-type: none"> • Universal Blu-ray DVD/CD Player • Upsamples to 4K Ultra HD • 3D Video • Built in decoding of Dolby True HD & DTS-HD Master Audio + legacy formats • Passes object-based 3D audio formats Dolby Atmos, DTS:X & Auro-3D to compatible processor • Fast Disc Loading • Quad Balanced 32-bit/192kHz DAC for stereo playback of CD/SACD/DVD-Audio discs • BD-Live & File Sharing Over Home Network 	59.995,00 kr.
MR87 	<ul style="list-style-type: none"> • AM/FM/HD Radio Tuner with Multi-Casting • XM-ready • Illuminated Analog Dial and 2-Line Multi-Function Fluorescent Display • Smooth-Acting, Weighted Tuning Mechanism with Animated Dial Pointer • Dual-Differential Remote AM Antenna • External AM and FM Antenna Inputs • 60 Station Presets (20 per band) • Balanced and Single-ended Analog Output • Coaxial and Optical Digital Audio Output 	47.895,00 kr.
MT10 	<ul style="list-style-type: none"> • Belt-Drive Turntable • Dural Aluminum Tone Arm • Weight-Matched Moving Coil Cartridge Included • Precision AC Motor • Magnetic Spindle Bearing • Strobe Speed Control • Illuminated Speed Meter • Multi-Layered Damped Chassis 	109.495,00 kr.
MT5 	<ul style="list-style-type: none"> • Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Magnetic Spindle Bearing • Multi-Layered Damped Chassis • Includes Plexi Dustcover 	69.995,00 kr.
MT2 	<ul style="list-style-type: none"> • Belt-Drive Turntable • Easy Set-up • Dural Aluminum Tone Arm • Plays 33-1/3 and 45 rpm records • High-Output Moving Coil Cartridge Included (compatible with Moving Magnet inputs) • Precision DC Motor • Resonance optimized and highly compressed wood base with black lacquer finish • Includes Plexi Dustcover 	44.795,00 kr.
MTI100 	<ul style="list-style-type: none"> • Belt-Drive Integrated Turntable • Includes: power amplifier, vacuum tube preamplifier, shielded phono preamplifier, 1 unbalanced auxiliary input, digital coaxial & optical inputs, Bluetooth receiver, subwoofer output, stereo speaker outputs, headphone jack • Plays 33-1/3 & 45 rpm records • Machined aluminum platter & tonearm • Anti-skate • Industrial grade permanent magnet AC synchronous motor with 2-speed pulley • Manual speed change • Includes Sumiko Olympia Moving Magnet cartridge • Class D amplifier: 80 Watts into 4 Ohms or 50 Watts into 8 Ohms 	64.995,00 kr.

INTEGRATED AUDIO SYSTEMS		
Unit	Description	DKK
RS200 	<ul style="list-style-type: none"> Next generation home audio wireless speaker • 650 Watts of total power • Two 4" x 6" woofers, four 2" midranges, two 3/4" tweeters • Apple® AirPlay® 2 • Bluetooth® 5.0 • DTS Play-Fi® (with built-in interfaces for streaming services including Amazon Prime Music, Pandora®, Qobuz, SiriusXM®, Spotify® & TIDAL) • DLNA • Works With Alexa • Qualcomm® aptX™ HD & Low Latency • USB, HDMI, Optical, & AUX inputs • Sub output • 3-position EQ switch • Connect TV for better sound 	29.895,00 kr.
RS100 	<ul style="list-style-type: none"> *NOT AVAILABLE IN ALL TERRITORIES • Wireless speaker featuring DTS Play-Fi technology • Start with 1 then add more to build system • Up to 16 can be added to a Wi-Fi network • Connect to existing Wi-Fi & then stream music library from mobile device via free Apple & Android app • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • AUX input for non-streaming use • Subwoofer output 	9.875,00 kr.
McAire 	<ul style="list-style-type: none"> Built in AirPlay® allows wireless streaming of music via Wi-Fi network from Mac or PC based iTunes® library, iPad®, iPhone® or iPod touch® • USB docking is available for all day playback and charging • Computers and TVs may be quickly connected for full range, high fidelity sound • Two 4" woofers, two 2" midranges, two 3/4" tweeters • Delivers the legendary McIntosh look and sound quality in a compact size 	28.975,00 kr.
MXA80 	<ul style="list-style-type: none"> Compact System • 2 x 50 Watts • Pair of specially designed 8 Ohm 2-way speakers • 6 Inputs: 4 Digital, 1 Balanced, 1 Unbalanced • 1 Preamp Output • 1 Headphone Jack (¼") • Uses Autoformer to produce 3 headphone impedance ranges of 8-40, 40-150 & 150-600 ohms • Headphone Crossfeed Director (HXD) images high quality recordings like conventional speakers • Power Guard to Prevent Clipping and Speaker Damage • 5 Step Bass Boost Control • Polished Stainless Steel Chassis 	58.495,00 kr.
MEDIA STREAMERS		
Unit	Description	DKK
MB50 	<ul style="list-style-type: none"> *NOT AVAILABLE IN ALL TERRITORIES • Streaming audio player featuring DTS Play-Fi technology • Connects to existing Wi-Fi to turn traditional audio system into a wireless audio system • Free Apple & Android app to stream music library stored on mobile device • App has built-in support for leading streaming services including Deezer, KKBox, Pandora, QQMusic, Rhapsody, SiriusXM, Songza, Spotify & TIDAL (subject to change) • Analog & digital inputs for mini-preamp functionality • Lossless playback of up to 16-bit/48kHz • Playback support for high-resolution music up to 24-bit/192kHz • Narrow chassis 	18.475,00 kr.
MS500 	<ul style="list-style-type: none"> Seamlessly integrates internet based streaming music & locally stored digital music into one comprehensive device • Up to 24 bit/192kHz output • Built-in interfaces to streaming services such as Deezer, Murfie, Pandora®, Rhapsody®, SiriusXM®, Slacker, Spotify® & TIDAL (list subject to change) • Ultra-quiet thanks to solid state drive & fanless processor with no noisy cooling fans • Synchronizes content stored on networked computers so it is readily playable • Secure back to Amazon Cloud Drive, Apple iCloud or Google Drive • Linux based OS • 3 USB ports to connect external drives • 1 additional independent audio zone can be created when using an external DAC 	59.995,00 kr.

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)		
Unit	Description	DKK
XRT2.1KL 	<ul style="list-style-type: none"> Reference Series Dual-Column 4-Way Ported Line-Source 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Left speaker only (see XRT2.1KR for matching right speaker) 	Pr. styk 645.995,00 kr. Pr. sæt 1.291.990,00 kr.
XRT2.1KR 	<ul style="list-style-type: none"> Reference Series Dual-Column 4-Way Ported Line-Source 81 Total Drivers • 6 x 8" Woofers • 2 x 6.5" Low Frequency Midranges • 28 x 2" Upper Frequency Midranges • 45 x 3" Tweeters • 12 Hz - 45 kHz Response • 90dB SPL • 2,000 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 7' (2.1 meters) tall • Piano Black finish • Right speaker only (see XRT2.1KL for matching left speaker) 	Pr. styk 645.995,00 kr. Pr. sæt 1.291.990,00 kr.
XRT1.1KL 	NEW • Dual-Column 4-Way Ported Line Array • 70 Total Drivers • 4 x 6.5" Woofers • 2 x 6.5" Low Frequency Midranges • 24 x 2" Upper Frequency Midranges • 40 x 3/4" Tweeters • 16 Hz - 45 kHz Response • 89dB SPL • 1,200 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 5.9' (1.8 meters) tall • Piano Black finish • Left speaker only (see XRT1.1KR for matching right speaker)	Pr. sæt 591.990,00 kr. Pr. styk 295.995,00 kr.
XRT1.1KR 	NEW • Dual-Column 4-Way Ported Line Array • 70 Total Drivers • 4 x 6.5" Woofers • 2 x 6.5" Low Frequency Midranges • 24 x 2" Upper Frequency Midranges • 40 x 3/4" Tweeters • 16 Hz - 45 kHz Response • 89dB SPL • 1,200 Watts Max Continuous Power • 8-Ohm Impedance • Solid Cinch™ speaker binding posts • 5.9' (1.8 meters) tall • Piano Black finish • Right speaker only (see XRT1.1KL for matching left speaker)	Pr. sæt 591.990,00 kr. Pr. styk 295.995,00 kr.

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)		
Unit	Description	DKK
CK200	In Wall Mounting Kit for XCS200	6.595,00 kr.
CS200 	<ul style="list-style-type: none"> In-Ceiling Loudspeaker • Perfect for custom installed distributed audio or as home theater surround sound speakers • 15 - 250 Watt Power Rating • 48Hz - 22kHz Response • 1 x 8" woven glass fiber woofer • 2 x 2" inverted Titanium dome midranges • 1 x 3/4" Titanium dome tweeter • Midranges and tweeter are housed in a rotating array • Paintable magnetic grille with minimum visible mounting flange • Voice matched to WS500 & WS300 speakers 	13.995,00 kr.
RK200	Construction Rough-In Kit for CS200	595,00 kr.
XR50 	<ul style="list-style-type: none"> True 3-Way Compact Bookshelf Speaker • 40 Hz - 45 kHz Frequency Response • 1 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 1 x 3/4" Titanium Super Tweeter • 300-Watt Music Power-Handling • Patented McIntosh Binding Posts • Front-Panel McIntosh Logo Illumination using Power Control • Premium cabinet finishes include Red Walnut, Gloss Black 	Pr. styk 19.995,00 kr. Pr. sæt 39.990,00 kr.
XR100 	<ul style="list-style-type: none"> True 4-way Floor-Standing Tower Speaker • 30 Hz - 45 kHz Frequency Response • 4 x 6" LDHP Woofers • 8 x 2" Titanium Midrange • 2 x 2" Titanium Tweeters • 1 x 3/4" Titanium Super Tweeter • Dual Sets of Patented McIntosh Binding Posts Enable Bi-Wire or Bi-Amplification • 600-Watt Music Power Handling • Front-Panel McIntosh Logo Illumination Using Power Control • Premium Cabinet Finishes Include Red Walnut, Gloss Black 	Pr. styk 47.995,00 kr. Pr. sæt 95.990,00 kr.
LCR80 	<ul style="list-style-type: none"> True 3-Way Center-Channel Speaker • 80Hz to 45 kHz Frequency Response 2 x 6" LDHP Woofer • 2 x 2" Titanium Mid/Tweeters • 1 x 3/4" Titanium Super Tweeter 300-Watt Music Power-Handling Voiced to Match XR50 & XR100 • Patented McIntosh Binding Posts Premium Cabinet Finishes include Red Walnut, Gloss Black (Pear Maple Discontinued) 	Pr. styk 23.995,00 kr.
HT30-IW 	<ul style="list-style-type: none"> IN-Wall THX Licensed Dipole Surround Speaker 200 Watts Max Continuous Power 2 x 5" Polypropylene Woofers • 2 x 1" Aluminum Dome Tweeters Paintable Frame & Metal Grill SOLD IN PAIRS	27.995,00 kr.
HT30-OW 	<ul style="list-style-type: none"> ON-Wall THX Licensed Dipole Surround Speaker 200 Watts Max Continuous Power 2 x 5" Polypropylene Woofers • 2 x 1" Aluminum Dome Tweeters Paintable Frame & Metal Grill SOLD IN PAIRS	27.995,00 kr.
RK100	Construction Rough-In Kit for CS100	450,00 kr.
WS300 	<ul style="list-style-type: none"> In-Wall 3-Way Loudspeaker • Perfect for custom installed distributed audio or home theater • 15 - 250 Watt Power Rating • 80Hz - 20kHz Response • 1 x 8" woven glass fiber woofer • 2 x 2" inverted Titanium dome midranges • 1 x 3/4" Titanium dome tweeter • Fully enclosed to deliver incredible performance in any environment • Fits in standard 2x4 wall construction • Paintable magnetic grille with minimum visible mounting flange • Voice matched to WS500 & CS200 speakers 	Pr. styk 24.995,00 kr.
RK300	Construction Rough-In Kit for WS300	595,00 kr.

LOUDSPEAKERS (Prices shown for most units are for EACH piece, Prs have *)		
Unit	Description	DKK
RK300	Construction Rough-In Kit for WS300	595,00 kr.
WS350 	<ul style="list-style-type: none"> • In-Wall 3-Way Speaker • 200 Watts Max Continuous Power Handling • 5-Tweeter Bessel Array • One 8" Woofer • One 4" Midrange • Five 1" Dome Tweeters • Deep-Drawn Sealed Aluminum Enclosure • Paintable Frame & Metal Grille 	Pr. styk 20.475,00 kr.
RK320	Construction Rough-In Kit for WS350	450,00 kr.
WS500 	<ul style="list-style-type: none"> • In-Wall 3-Way Loudspeaker • Perfect for custom installed distributed audio or home theater • 15 - 250 Watt Power Rating • 80Hz - 20kHz Response • 2 x 6-1/2" woven glass fiber woofers • 2 x 2" inverted Titanium dome midranges • 1 x 3/4" Titanium dome tweeter • Fully enclosed to deliver incredible performance in any environment • Fits in standard 2x4 wall construction • Paintable magnetic grille with minimum visible mounting flange • Voice matched to WS300 & CS200 speakers 	Pr. styk 28.995,00 kr.
RK500	Construction Rough-In Kit for WS500	595,00 kr.
ACCESSORIES		
Unit	Description	DKK
MPC1500 	<ul style="list-style-type: none"> • AC Isolation Transformer & AC Switching Hub • 12 Rear Panel AC Outlets with Programmable Power Control Options • Front and Rear Panel LED Status Indicators • Front Panel Back-Lit Meters Display Line Voltage & Amperage 	53.995,00 kr.
MPC500 	<ul style="list-style-type: none"> • AC power line surge protection via 3 thermally protected metal-oxide varistors (TPMOVs) • Secondary surge protection of ethernet, coaxial, & other low voltage devices via Gas Discharge Tubes (GDT), Positive Temperature Coefficient (PTC) thermistors and Transient Voltage Suppression (TVS) components • Connect 4-8 components depending on receptacle type • Electromagnetic interference (EMI) filtering • Over/under voltage protection • Display lists input voltage, current draw, or total power 	23.895,00 kr.
MC CLOCK 	The McIntosh Clock boast our trademak glass front pannel and two of our blue meters , One to show the hour and the other to show minutes.	17.995,00 kr.
LB100 	Unmistakably McIntosh. The LB100 Light Box proudly displays the "Handcrafted In The USA Since 1949" statement as a badge of honor. A must for every McIntosh owner. Approximately the size of a McIntosh CD player. Includes Power Control for seamless on/off with other McIntosh components.	13.300,00 kr.
BLI-23 (pair)	Balanced Line Integrator, 2 XLR Inputs & 3 XLR Outputs	2.795,00 kr.
MCBOOK 	"For the Love of Music" -- The History of McIntosh	1.350,00 kr.
DA2 Upgrade Kit 	NEW • Dealer installed upgrade to DA1 Digital Audio Module • Models that can be upgraded to DA2: MA9000, MA8900, MA7200, MA5300, MAC7200, C49 • 7 inputs: 2 Optical, 2 Coax, 1 USB, 1 MCT, 1 HDMI (ARC) • DSD512 & DXD 384kHz support • Audiophile-grade 8-channel, 32-bit DAC • Due to the technical nature of the DA2 upgrade, the upgrade must be performed by a qualified trained professional at an Authorized McIntosh Dealer or Authorized McIntosh Service Agency	9.900,00 kr.
TM3 Tuner Module 	<ul style="list-style-type: none"> • AM/FM/HD Radio Tuner Module for use with MA6600 Integrated Amplifier • Includes Dual-Differential Remote AM Antenna • External AM and FM antenna inputs 	7.700,00 kr.

AUDIO CABLES		
Unit	Description	DKK
CBA1M	BALANCED AUDIO SINGLE 1-METER	3.795,00 kr.
CBA2M	BALANCED AUDIO SINGLE 2-METER	4.800,00 kr.
CA1M	UNBALANCED AUDIO PAIR 1-METER	5.795,00 kr.
CA2M	UNBALANCED AUDIO PAIR 2-METER	6.595,00 kr.
CDA1M	COAX DIGITAL SINGLE 1-METER	4.450,00 kr.
CDA2M	COAX DIGITAL SINGLE 2-METER	5.300,00 kr.
CC1M	CONTROL SINGLE 1-METER	645,00 kr.
CC2M	CONTROL SINGLE 2-METER	745,00 kr.
CS2M	SPEAKER SINGLE 2-METER	10.995,00 kr.
CS3M	SPEAKER SINGLE 3-METER	13.995,00 kr.

PS AUDIO SCANDINAVIA

DER TAGES FORBEHOLD FOR TRYK- OG TASTEFEJL, PRISÆNDRINGER OG UDSOLGTE VARER.